

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Intent of Specifications

It is the intent of these specifications to cover the furnishing and delivery to the purchaser of a complete vehicle equipped as hereinafter specified. With a view to obtaining the best results and the most acceptable apparatus, these specifications cover minimum requirements as to the type of construction, finish, and tests to which the apparatus must conform, together with certain details as to equipment and appliances to be furnished. Minor details of construction and materials, where not otherwise specified, are left to the discretion of the contractor, who shall be solely responsible for the design and construction. The apparatus shall conform to the requirements of the current (at the time of bid) NFPA Standard for Pumper apparatus to the extent as specified herein.

Qualification of Bidders

Bids will only be considered on vehicles constructed in the continental United States, whose manufacturers have an established reputation of permanency and reliability in the field of fire apparatus construction. Each manufacturer shall furnish satisfactory evidence of their ability to construct the apparatus as specified, and shall state the location of the factory where the complete apparatus will be built.

- ◆ How long has the manufacturer been building chassis at this location?

Number of years:

- ◆ How long has the manufacturer been building bodies at this location?

Number of years:

Service Requirements

It is the intent of the purchaser to assure that parts and service are readily available for the apparatus specified. SERVICE CAPABILITIES WILL BE A MAJOR CRITERIA FOR AWARD OF THIS BID. To insure proper service, no bid will be accepted unless the bidder owns or offers facilities within seventy-five (75) miles where complete parts and service are available. The facility must be staffed by full time personnel who are factory trained and EVT certified in the operation and repair of the fire apparatus with full authorization of the manufacturer. In addition, in order to ensure prompt service, the facility must be solely dedicated to the service/repair of emergency vehicles. The facility shall maintain a complete inventory including body components, electrical items, fire apparatus hardware, etc., and shall offer on-site services including pump overhaul, body fabrication, collision repair, and a paint shop complete with a cross flow booth with air makeup and bake options to insure the highest quality paint finish available. Bids from manufacturers who use third party service people or facilities, or who do not offer a service center will be immediately rejected. Furthermore, due to a concern over having vehicles "out-of-service" for extended periods of time as a result of having to be sent back to the original manufacturer's location for repairs, any bidder who cannot

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

guarantee that all future repairs will be handled at a local level will not be acceptable.

Emergency Vehicle Technician Qualifications

Due to the highly specialized nature of fire apparatus repair, emergency vehicle technicians employed by the bidder shall be in conformance with NFPA standards 1915 and 1071. The bidder shall employ at least one (1) technician certified as a "Master Mechanic" (having amassed every EVT certification). Proof of current certification shall be supplied with the bid. There shall be no exceptions to this requirement. Bids from organizations that do not meet these requirements shall be immediately rejected.

Service Questionnaire

The bidder shall include the following information with their bid.

- ◆ Number of miles from the purchaser to the nearest staffed service facility owned and operated by the bidder

Number of miles:

- ◆ The number of service bays and square feet of service space at the bidder's service facility.

Number of bays: Square feet:

- ◆ The length of time the service facility has been in business as an emergency vehicle dealer.

Number of years in business:

- ◆ How long has the dealer been selling the brand of emergency vehicle being proposed?

Number of years:

- ◆ Has the dealer/distributor represented other manufacturers of emergency vehicles in the past?

Yes/No

- ◆ Number of aerial platforms that have been delivered by the dealer/distributor since it has been in business representing its current "brand(s)" of emergency vehicles?

Number of aerial platforms delivered:

- ◆ Is the dealership strictly dedicated to selling and servicing emergency vehicles and equipment, or do they sell and service other products?

Strictly dedicated to emergency vehicles and equipment?

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

- ◆ Number of EVT Certified personnel employed? EVT "Master Mechanics"?

EVT certified personnel: EVT Master Mechanic:

- ◆ Number of full-time mechanics employed by the bidder that are solely dedicated to servicing emergency vehicles?

Number solely dedicated to emergency vehicle service:

- ◆ Full body/collision repair, fabrication, and paint booth on-site?

Yes/No

- ◆ Over \$400,000 in parts inventory available at all times?

Yes/No

- ◆ Does the local service facility accept work on other vehicles (i.e., DPW, oil, concrete, etc.) or fleet trucks in addition to emergency vehicles on a regular basis?

Yes/No

- ◆ Does the possibility exist that the emergency vehicle may have to go back to the original manufacturer's location for warranty work?

Yes/No

- ◆ Does the dealer/distributors service facility perform ALL warranty work for the products they represent?

Yes/No

- ◆ Does the dealer offer mobile service that can respond to a "priority service call" within (48) hours?

Yes/No

Delivery

The apparatus shall be delivered under its own power to assure adequate break-in while under warranty. It shall first be transported to the local service facility, where final inspection and preparation will be performed, including mounting of related equipment. The apparatus will then be delivered to the Purchaser's location.

Post-Delivery Training

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

On one (1) mutually agreeable date after delivery, a certified delivery engineer shall familiarize those persons designated by the Fire Chief with the basic operation of the apparatus and its components. Such training must be coordinated by a fire department officer with a minimum of 20 years of "hands on" experience on the fire ground. This shall be a full instructional program including both classroom and practical or "hands on" training. Limited programs or "drop-off" type deliveries are unacceptable.

Maintenance Training

A training session shall be provided to familiarize a designated person of the various service/maintenance requirements on this unit.

Construction Time

The completed apparatus shall be delivered within three hundred thirty (330) days.

Approval Drawings

A general arrangement drawing depicting the vehicles appearance shall be provided. The drawing shall consist of left side, right side, front, and rear elevation views.

Vehicles requiring pump controls shall include a general arrangement view of the pump operator's position, scaled the same as the elevation views.

Electronic Manuals

Two (2) copies of all operator, service, and parts manuals must be supplied at the time of delivery in digital format. The electronic manuals shall include the following information:

- Operating Instructions, descriptions, specifications, and ratings of the cab, chassis, body, aerial (if applicable), installed components, and auxiliary systems.
- Warnings and cautions pertaining to the operation and maintenance of the fire apparatus and firefighting systems.
- Charts, tables, checklists, and illustrations relating to lubrication, cleaning, troubleshooting, diagnostics, and inspections.
- Instructions regarding the frequency and procedure for recommended maintenance.
- Maintenance instructions for the repair and replacement of installed components.
- Parts listing with descriptions and illustrations for identification.
- Warranty descriptions and coverage.

The electronic document shall incorporate a navigation page with electronic links to the operator's manual, service manual, parts manual, and warranty information, as well as instructions on how to use the manual. Each copy shall include a table of contents with links to the specified documents or illustrations.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The electronic document must be formatted in such a manner as to allow not only the printing of the entire manual, but to also the cutting, pasting, or copying of individual documents to other electronic media, such as electronic mail, memos, and the like.

A find feature shall be included to allow for searches by text or by part number.

These electronic manuals shall be accessible from any computer operating system capable of supporting portable document format (PDF). Permanent copies of all pertinent data shall be kept file at both the local dealership and at the manufacturer`s location.

NOTE: Engine overhaul, engine parts, transmission overhaul, and transmission parts manuals are not included.

Fire Apparatus Safety Guide

Fire Apparatus Safety Guide published by FAMA, latest edition. This safety manual is intended to point out some of the basic safety situations that may be encountered during the normal operation and maintenance of a fire apparatus and to suggest possible ways of dealing with these situations. This manual is NOT a substitute for the E-ONE`s fire apparatus operator and maintenance manuals or commercial chassis manufacturer`s operator and maintenance manuals.

Hosebed Capacity

The hosebed shall have the capacity to store the following hose from the driver side to the officer side – 200’ 1.75” DJ, 250’ 1.75” DJ, 1000’ 5” LDH, 500’ 3” DJ and 400’ 2” DJ hose.

NFPA Compliance

The supplied components of the apparatus shall be compliant with NFPA 1901, 2016 edition.

Equipment Capacity

Equipment allowance on the apparatus shall be 2500 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.

Front Bumper Extension

The bumper shall be extended approximately 20” from the face of the cab as required.

Bumper

A heavy duty 10" high steel channel type front bumper shall be provided. The front corners of the bumper shall be angled to reduce swing clearance. The driver side of the bumper shall have a notch to allow room for a flush mounted Q2B siren.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The bumper shall be painted job color.

Bumper Gravel Shield

The extended front bumper gravel shield shall be made of 3/16" (.188") aluminum treadplate material. The gravel shield shall include 1" turn down lips to protect the top edge of the heavy duty bumper from damage.

Bumper Hose Tray Lid

The center bumper tray shall have a diamond plate lid. The lid shall be hinged and include a latch, rubber seal and held open with a pneumatic shock.

Bumper Tray - Center

A hose tray constructed of 1/8" aluminum shall be recessed into the front bumper extension. The tray shall be located in the center of the bumper and be approximately 14" deep (13" to the top of the slats). One inch thick aluminum slats shall be included in the bottom of the hose tray to aid in the dissipation of water from the tray. Tray shall have the capacity to hold 150' of 1.75" attack hose and nozzle

Hose Tray Lid Notch

The front bumper hose tray lid shall be notched to allow for preconnected hose.

The notch shall be: 4" front to rear x 3" side to side centered on officer side of center tray lid.

Rear Underbody Support Frame

The body shall be supported at the rear by a steel frame extension bolted to the chassis frame rails. The frame rails and frame extension shall be isolated from the aluminum body extrusions by 5/16" x 2" fiber reinforced rubber.

The frame extension shall be built with (2) 2.5" sq. x .25 wall thickness x full width cross rails welded to (2) 2.5" sq. x .25 wall thickness side rails. The frame extension assembly will be welded to steel weldments, which are secured to the chassis frame with grade 8 5/8" bolts. The frame shall have a hot-dipped galvanized zinc coating in place of standard for increased corrosion resistance. The coating shall be done in compliance with the ASTM A123 Standard.

The frame extension shall not interfere with N.F.P.A. minimum requirements for angle of departure.

Frame Assembly

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The frame shall consist of two (2) C-channel frame rails with heavy-duty cross-members. Each frame rail shall have the following minimum specifications in order to minimize frame deflection under load and thereby improve vehicle ride and extend the life of the frame:

Dimensions: 10-1/4" x 3-1/2" x 3/8"

Material: 110,000-psi minimum yield strength, high strength, low alloy steel

Section Modulus: 16.61 cu. in.

Resistance to Bending Moment (RBM): 1,827,045 in. lbs.

If larger rails are provided, the maximum height of each frame rail shall not exceed the 10-1/4" dimension by more than 1/2" in order to ensure the lowest possible body height for ease of access as well as the lowest possible vehicle center of gravity for maximum stability.

There shall be a minimum of six (6) cross-members joining the two (2) frame rails in order to make the frame rigid and hold the rails/liners in alignment. The cross-members shall be a combination of a formed steel C-channel design along with heavy duty steel fabricated designs as required for the exact chassis configuration. The cross-members shall be attached to the frame rails with not less than four (4) bolts at each end arranged in a bolt pattern to adequately distribute the cross-member load into the rail/liner and minimize stress concentrations.

All frame fasteners shall be high-strength Grade 8, flanged-head threaded bolts and nuts for frame strength, durability, and ease of repair. The nuts shall be Stover locknuts to help prevent loosening. The frame fasteners shall be tightened to the proper torque at the time of assembly.

The frame rails shall be hot-dip galvanized and powder coated for improved corrosion resistance. The galvanization shall be a minimum of 4 mils thick and done in accordance with ASTM A123. The powder coat shall be 6.5 mils thick (+/- 1.5 mils) and pass ASTM D3359 testing.

The frame cross-members and frame mounted components (suspensions, axles, air tanks, battery boxes, fuel tank, etc.) shall be painted black.

The apparatus manufacturer shall supply a full lifetime frame warranty including cross-members against defects in materials or workmanship. Warranties that provide a lifetime warranty for only the frame rails, but not the cross-members, are not acceptable.

The custom chassis frame shall have a wheel alignment in order to achieve maximum vehicle road performance and to promote long tire life. The alignment shall conform to the manufacturer's internal specifications. All wheel lug nuts and axle U-bolt retainer nuts shall be tightened to the proper torque at the time of alignment. The wheel alignment documentation shall be made available at delivery upon request.

Galvanized Frame Components

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

The front chassis frame extensions, rear subframe, crossmembers and battery brackets shall be hot-dip galvanized for increased corrosion resistance. The coating shall be done in compliance with the ASTM A123 Standard.

Coated Fasteners

The custom chassis frame assembly shall be assembled using GEOMET 720 coated fasteners for corrosion resistance.

Shock Absorbers Front

Koni model 90 shock absorbers shall be provided for the front axle. The shocks shall be three way adjustable.

The shocks shall be covered by the manufacturer`s standard warranty.

Rear Axle

The vehicle shall be equipped with an ArvinMeritor RS-25-160 single rear axle with single-reduction hypoid gearing and a manufacturer`s rated capacity of 27,000 lbs. The axle shall be equipped with oil-lubricated wheel bearings with ArvinMeritor oil seals.

The rear axle hubs shall be made from ductile iron and shall be designed for use with 10 hole hub-piloted wheels to improve wheel centering and extend tire life.

A 2-year/unlimited miles parts and 2-year labor rear axle warranty shall be provided as standard by ArvinMeritor Automotive.

Front Axle

The vehicle shall utilize an ArvinMeritor FL-941 front axle with a rated capacity of 19,840 lbs. It shall have "easy steer" knuckle pin bushings and 68.5" kingpin centers. The axle shall be of I-beam construction and utilize grease-lubricated wheel bearings. The vehicle shall have a nominal cramp angle of 45 degrees, plus two (+ 2) degrees to minus three (- 3) degrees including front suction applications.

The front axle hubs shall be made from ductile iron and shall be designed for use with 10 hole hub-piloted wheels in order to improve wheel centering and extend tire life.

The front springs shall be parabolic tapered, minimum 4" wide x 54" long (flat), minimum 3 leaf, progressive rate with bronze bushings and a capacity of 20,000 lbs. at the ground.

Tapered leaf springs provide a 20% ride improvement over standard straight spring systems. Supporting documentation/data shall be provided upon request.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The vehicle shall be equipped with a Sheppard model M-110 power steering gear, used in conjunction with a power assist cylinder. The steering assembly shall be rated to statically steer up to a maximum front axle load of 19,840 lbs. Relief stops shall be provided to reduce system pressure upon full wheel cut. The system shall operate mechanically should the hydraulic system fail.

A 2-year/unlimited miles parts and 2-year labor axle warranty shall be provided as standard by ArvinMeritor Automotive.

In order to achieve maximum vehicle road performance and to promote long tire life, there shall be a wheel alignment. The alignment shall conform to the manufacturer`s internal specifications. All wheel lug nuts and axle U-bolt retainer nuts shall be tightened to the proper torque at the time of alignment. The wheel alignment documentation shall be made available at delivery.

Rear Suspension

The rear suspension shall be a pair of linear-rate leaf springs with auxiliary “helper” leaf springs and bronze bushings. The variable-rate springs with auxiliary springs ensure that the vehicle rides and handles smoothly under both loaded and unloaded conditions. The suspension shall be rated for the maximum axle capacity.

Front Wheels

The front wheels shall be steel hub-piloted disc sized appropriately for the tires.

Rear Wheels

There shall be four hub-piloted steel disc wheels sized appropriately for the tires.

Valve Stem Extensions

Each inside rear wheel on the rear axle shall have valve extensions.

Wheel Checks

High temperature orange Wheel Check loose lug nut indicators shall be provided on each of the units wheels.

Front Tires

The front tires shall be two (2) Michelin 385/65R22.5 tubeless radial tires with X MULTIWAY HD XZE highway tread.

The tires with wheels shall have the following weight capacity and speed ratings:

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Up to 22,000 lbs. @ 68 MPH (steel or aluminum wheels)

The wheels and tires shall conform to the Tire and Rim Association requirements.

Rear Tires

The rear tires shall be Michelin 12R22.5 tubeless type radial tires with XDN2 all weather tread.

The tires with wheels shall have the following weight capacity:

27,000 lbs. (dual) @ 75 MPH

The wheels and tires shall conform to the Tire and Rim Association requirements.

Tire Pressure Monitor

The apparatus shall be provided with tire pressure indicating valve stem caps. The indicators shall be installed on each tire and be a heavy duty design manufactured specifically for trucks. When tire is properly inflated, the indicator inside the cap shall be green, and when the tire is underinflated by 10%, the indicator inside the cap shall be red.

Front Brakes

The front axle shall be equipped with Meritor DiscPlus EX225H 17 inch disc brakes.

The brakes shall be covered by the manufacturer`s standard warranty which is two years, unlimited mileage and parts only.

Rear Brakes

The rear axle shall be equipped with Meritor DiscPlus EX225H 17 inch disc brakes with a maximum rated capacity of 27,000 lbs.

The brakes shall be covered by the manufacturer`s standard warranty which is two years, unlimited mileage and parts only.

Brake System

The vehicle shall be equipped with air-operated brakes and an anti-lock braking system (ABS). The brake system shall meet or exceed the design and performance requirements of the current Federal Motor Vehicle Safety Standard (FMVSS)-121, and the test requirements of the current NFPA 1901 Standard.

A dual-treadle brake valve shall correctly proportion the braking power between the front and rear systems. The air system shall be provided with a rapid pressure build-up feature, designed

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

to meet current NFPA 1901 requirements, to allow the vehicle to begin its emergency response as quickly as possible.

A pressure-protection valve shall be installed to prevent use of the air horns or other air-operated devices should the air system pressure drop below 85 psi. This feature is designed to prevent inadvertent actuation of the emergency/parking brakes while the vehicle is in motion.

Two (2) air pressure needle gauges, one (1) each for front and rear air pressure, with a warning light and buzzer shall be installed at the driver`s instrument panel.

The braking system shall be provided with a minimum of three (3) air tank reservoirs for a total air system capacity of 5,214 cu. in. One (1) reservoir shall serve as the wet tank and a minimum of one (1) tank shall be supplied for each of the front and rear axles. The total system shall carry a sufficient volume of air to comply with FMVSS-121.

Tank Capacities in Cubic Inches:

Wet	Front	Rear	Total
1,738	1,738	1,738	5,214

Spring-actuated emergency/parking brakes shall be installed on the rear axle.

A Bendix-Westinghouse SR-1 valve, in conjunction with a double check valve system, shall provide automatic emergency brake application when the air brake system pressure falls below 40 psi in order to safely bring the vehicle to a stop in case of an accidental loss of braking system air pressure.

A four-channel Wabco ABS shall be provided to improve vehicle stability and control by reducing wheel lock-up during braking. This braking system shall be fitted to both front and rear axles. All electrical connections shall be environmentally-sealed for protection against water, weather, and vibration.

The system shall constantly monitor wheel behavior during braking. Sensors on each wheel transmit wheel speed data to an electronic processor, which shall detect approaching wheel lock-up and instantly modulate (or pump) the brake pressure up to five (5) times per second to prevent wheel lock-up. Each wheel shall be individually controlled. To improve field performance, the system shall be equipped with a dual-circuit design configured in a diagonal pattern. Should a malfunction occur in one circuit, that circuit shall revert to normal braking action. A warning light at the driver`s instrument panel shall signal a malfunction.

The system shall also be configured to work in conjunction with all auxiliary engine, exhaust, or driveline brakes to prevent wheel lock-up.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

To improve maintenance troubleshooting, provisions in the system for an optional diagnostic tester shall be provided. The system shall test itself each time the vehicle is started, and a dash-mounted light shall go out once the vehicle is moving above 4 MPH.

A 3 year/300,000 mile parts and labor Anti-Locking Braking System (ABS) warranty shall be provided as standard by Meritor Automotive.

Park Brake Release

One (1) Bendix-Westinghouse PP-5 parking brake control valve shall be supplied on the lower dash panel within easy reach of the driver.

Electronic Stability Control

The apparatus shall be equipped with a G4 4S4M Electronic Stability Control (ESC) system that combines the functions of Roll Stability Control (RSC) with the added capability of yaw - or rotational – sensing.

RSC focuses on the vehicle's center of gravity and the lateral acceleration limit or rollover threshold. When critical lateral acceleration thresholds are exceeded, RSC intervenes to regulate the vehicle's deceleration functions. The added feature of ESC is to automatically intervene to reduce the risk of the vehicle rotating while in a curve or taking evasive action, prevents drift out through selective braking, and controlling and reducing vehicle speed when lateral acceleration limits are about to be exceeded.

Intervention by the system occurs in three forms - engine, retarder and brake control. The ESC system uses several sensors to monitor the vehicle. These include a steering wheel angle sensor, lateral accelerometer, and yaw position sensor. ESC constantly monitors driving conditions and intervenes if critical lateral acceleration is detected or if the vehicle begins to spin due to low friction surfaces. The system provides control of engine and retarder torque as well as automatically controlling individual wheels to counteract both over steer and under steer.

To further improve vehicle drive characteristics, the unit shall be fitted with Automatic Traction Control (ATC). This system shall control drive wheel slip during acceleration from a resting point. An extra solenoid valve shall be added to the ABS system. The system shall control the engine and brakes to improve acceleration slip resistance. The system shall have a dash mounted light that shall come on when ATC is controlling drive wheel slip.

3 year/300,000 miles parts and labor warranties for ESC, RSC, and ATC shall be provided as standard by Meritor Automotive.

Brake System Fittings

All air brake system hoses on the chassis shall be connected by use of compression fittings. Includes air lines in the chassis cab (if equipped).

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Air Dryer

The chassis air system shall be equipped with a Bendix-Westinghouse AD-9 air dryer to remove moisture from the air in order to help prevent the air lines from freezing in cold weather and prolong the life of the braking system components.

Air Inlet

A 1/4" brass quick-release air inlet with a male connection shall be provided. The inlet shall allow a shoreline air hose to be connected to the vehicle, discharging air directly into the wet tank of the air brake system. It shall be located driver door jamb.

Air Lines

Air brake lines shall be constructed of color coded nylon tubing routed in a manner to protect them from damage. Brass fittings shall be provided.

Air Horns

Dual Grover air horns shall be provided, connected to the chassis air system. The horns shall be mounted through the front bumper. The front bumper shall have two (2) holes punched to accommodate the horns. A pressure protection valve shall be installed to prevent the air brake system from being depleted of air pressure.

Transmission Selector

A push-button transmission shift module, Allison model 29538373, shall be located to the right side of the steering column within easy reach of the driver. The shift position indicator shall be indirectly lit for after dark operation. The shift module shall have a "Do Not Shift" light and a "Service" indicator light. The shift module shall have means to enter a diagnostic mode and display diagnostic data including oil life monitor, filter life monitor, transmission health monitor and fluid level. A transmission temperature gauge with warning light and buzzer shall be installed on the cab instrument panel.

Transmission Fluid

The transmission fluid shall be TransSynd synthetic.

Vehicle Speed

The maximum speed shall be electronic limited to 68 MPH as required by NFPA 1901.

Note: Maximum speed may be set at 65 MPH due to tire rating.

Engine/Transmission Package

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Engine

The vehicle shall utilize a Cummins L9 engine as described below:

- 450 maximum horsepower at 2100 rpm
- 1250 lb-ft peak torque at 1400 rpm
- Six (6) cylinder, charge air cooled, 4-cycle diesel
- 543 cu. in. (8.9 liter) displacement - 4.49 in bore x 5.69 in stroke
- 16.6:1 compression ratio
- Viable Geometry Turbocharged
- Engine shall be equipped with Full-Authority Electronics
- Electronic Timing Control fuel system
- Fuel cooler (when equipped with a fire pump)
- Fleetguard FS1022 fuel filter with integral water separator and water-in-fuel sensor approved by Cummins for use on the ISL engine
- Fleetguard LF9009 Venturi Combo combination full-flow/by-pass oil filter approved by Cummins for use on the ISL engine
- Engine lubrication system, including filter, shall have a minimum capacity of 25 quarts
- Delco-Remy 39 MT-HD 12-volt starter
- Cummins 18.7 cubic foot per minute (cfm) air compressor
- Corrosion inhibitor additive for coolant system
- After treatment system consisting of a oxidation catalyst and diesel particulate filter and selective catalyst reduction system
- Ember separator compliant with current NFPA 1901 standard
- The engine shall be compliant with 2017 EPA Emission standards

The engine air intake shall draw air through the front cab grill. The intake opening shall be located on the officer (right) side behind front cab face with a plenum that directs air to the air filter. The air cleaner intake piping shall be made from aluminized steel tubing with flexible rubber hoses. The intake piping clamps shall be heavy-duty, constant-torque, T-bolt style to ensure proper sealing under all temperatures in order to keep dust and other contaminants out of the engine intake air stream and protect the engine.

The air cleaner shall be an 11” diameter K&N for lower restriction and high air flow. The filtration media shall be washable and easily accessed for service. The air filter shall have a 3 year / 300,000 mile warranty.

The engine exhaust piping shall be a minimum of 4” diameter welded stainless steel tubing. The aftertreatment system shall be mounted horizontally under the right-hand frame rail in back of the cab in order to minimize heat transmission to the cab and its occupants. The exhaust shall be directed away from the vehicle on the right side ahead of the rear wheels in order to keep exhaust fumes as far away as possible from the cab and pump operator position.

A 5-year/100,000-miles parts and labor warranty shall be provided as standard by Cummins.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

A copy of the Engine Installation Review stating the engine installation meets Cummins recommendations shall be provided as requested. The engine installation shall not require the operation of any type of "power-down" feature to meet engine installation tests.

Transmission

The vehicle shall utilize an Allison EVS3000P, electronic, 5-speed automatic transmission.

A push button shift module shall be located right side of the steering column, within easy reach of the driver. The shift position indicator shall be indirectly lit for after-dark operation. The shift module shall have a "Do Not Shift" light and a "Service" indicator light that are clearly visible to the driver. The shift module shall have means to enter a diagnostic mode and display diagnostic data.

A transmission oil temperature gauge with warning light and buzzer shall be installed on the cab instrument panel to warn the driver of high oil temperatures that may damage the transmission.

The transmission shall have a gross input torque rating of 1250 lb.-ft. and a gross input power rating of 450 HP.

The gear ratios shall be as follows:

1 - 3.49

2 - 1.86

3 - 1.41

4 - 1.00

5 - .75

R - 5.03

The transmission shall have an oil capacity of 23 quarts and shall be equipped with a fluid level sensor (FLS) system, providing direct feedback of transmission oil level information to the driver.

A water-to-oil transmission oil cooler shall be provided to ensure proper cooling of the transmission when the vehicle is stationary (no air flow). Air-to-oil transmission oil coolers, which require constant air flow, are not acceptable.

The transmission shall be provided with two (2) engine-driven PTO openings located at the 4 o'clock and 8 o'clock positions for flexibility in installing pto-driven equipment.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The automatic transmission shall be equipped with a power lock-up device. The transmission lock-up shall prevent down shifting of the transmission when the engine speed is decreased during pump operations, thereby maintaining a constant gear ratio for safe operation of the pump. The transmission lock-up shall be automatically activated when the pump is engaged in gear. The transmission lock-up shall be automatically deactivated when the pump is disengaged for normal road operation.

A 5-year/unlimited miles parts and labor warranty shall be provided as standard by Allison Transmission.

Automatic Shift to Neutral

The transmission shall be programmed to comply with NFPA 1901 and automatically shift to neutral upon application of the parking brake.

Jacobs Engine Brake

One (1) Jacobs engine brake shall be installed to assist in slowing and controlling the vehicle as required by NFPA 1901 for vehicles with gross vehicle weight ratings (GVWR) of 36,000 lbs. or greater. An on-off control switch and a high-medium-low selector switch shall be mounted in the cab accessible to the driver.

When activated, the Jacobs engine brake shall cut off the flow of fuel to the cylinders and alter the timing of the exhaust valves. This shall transform the engine into a high-pressure air compressor, driven by the wheels, and the horsepower absorbed by the engine in this mode shall slow the vehicle. The selector switch allows the driver to select the amount of retarding power.

When the on-off switch is in the “on” position, the engine brake shall be automatically applied whenever the accelerator is in the idle position and the automatic transmission is in the lock-up mode. If the accelerator is depressed or if the on-off switch is placed in the “off” position, the engine brake shall immediately release and allow the engine to return to its normal function.

Transmission Programming

The transmission shall include the Allison 2nd gear Pre-Select feature. This option will direct the transmission to down shift to second gear when the throttle is released and the Jacobs engine brake is engaged. This feature is designed to increase brake life and aid vehicle braking.

Exhaust End Modification

The end of the exhaust tail pipe shall be modified to accommodate a Plymovent in-house exhaust extraction system. The tail pipe will be at 90 degrees and straight out below the side of body. A stop ring shall be provided on the tail pipe to properly position the Plymovent nozzle. The exhaust outlet shall be vented for use with 2013 and newer EPA engines.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Engine Cooling Package

Radiator

The cooling system shall include an aluminum tube-and-fin radiator with a minimum of 1,408 total square inches of frontal area to ensure adequate cooling under all operating conditions. There shall be a drain valve in the bottom tank to allow the radiator to be serviced. A sight glass shall be included for quick fluid level assessment. The radiator shall be installed at the prescribed angle in order to achieve the maximum operational effectiveness. This shall be accomplished according to established work instructions and properly calibrated angle measurement equipment.

Silicone Hoses

All radiator and heater hoses shall be silicone. Pressure compensating band clamps shall be used to eliminate hose pinching on all hoses 3/4" diameter and larger. All radiator hoses shall be routed, loomed, and secured so as to provide maximum protection from chafing, crushing, or contact with other moving parts.

Coolant

The cooling system shall be filled with a 50/50 mixture of water and antifreeze/coolant conditioner to provide freezing protection to minus 40 (- 40) degrees F for operation in severe winter temperatures.

Coolant Recovery

There shall be a coolant overflow recovery system provided.

Charge Air Cooler System

The system shall include a charge air cooler to ensure adequate cooling of the turbocharged air for proper engine operation and maximum performance.

Charge Air Cooler Hoses

Charge air cooler hoses shall be made from high-temperature, wire-reinforced silicone to withstand the extremely high temperatures and pressures of the turbocharged air. The hoses shall incorporate a flexible hump section to allow motion and misalignment of the engine relative to the charge air cooler. Charge air cooler hose clamps shall be heavy-duty, constant-torque, T-bolt clamps to ensure proper sealing under all temperatures in order to keep dust and other contaminants out of the engine intake air stream and protect the engine.

Fan/Shroud

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

The fan shall be 30" in diameter with eleven (11) blades for maximum airflow and dynamic balance. It shall be made of nylon for strength and corrosion resistance. The fan shall be installed with grade 8 hardware which has been treated with thread locker for additional security. A fan shroud attached to the radiator shall be provided to prevent recirculation of engine compartment air around the fan in order to maximize the cooling airflow through the radiator. The fan shroud shall be constructed of fiber-reinforced high temperature plastic. The shroud shall be specifically formed with curved surfaces which improves air flow and cooling.

Transmission Cooler

The cooling system shall include a liquid-to-liquid transmission cooler capable of cooling the heat generated from the transmission. When a transmission retarder is selected, the cooler shall have an increased capacity to handle the additional heat load.

Fuel System

One (1) 65 gallon fuel tank shall be provided. The tank shall be of an all-welded, aluminized-steel construction with anti-surge baffles and shall conform to all applicable Administration (FHWA) 393.65 and 393.67 standards. The tank shall be mounted below the frame rails at the rear of the chassis for maximum protection. The tank shall be secured with two (2) wrap-around T-bolt type stainless steel straps. Each strap shall be fitted with protective rubber insulation and shall be secured with Grade 8 hardware. This design allows for tank removal from below the chassis.

The fuel tank shall be equipped with a 2" diameter filler neck. The filler neck shall extend to the rear of the vehicle behind the rear tires and away from the heat of the exhaust system as required by NFPA 1901 Standard for Automotive Fire Apparatus. The open end of the filler neck shall be equipped with a twist-off filler cap with a retaining chain.

The tank shall be plumbed with top-draw and top-return fuel lines in order to protect the lines from road debris. Bottom-draw and/or bottom-return fuel lines are not acceptable. A vent shall be provided at the top of the tank. The vent shall be connected to the filler neck to prevent splash-back during fueling operations. A .50" NPT drain plug shall be provided at the bottom of the tank.

The tank shall have a minimum useable capacity of 65 gallons of fuel with a sufficient additional volume to allow for thermal expansion of the fuel without overflowing the vent.

A fuel pump shall be provided and sized by the engine manufacturer as part of the engine.

Fuel Line Hose

Wire braided fuel hose meeting SAE J-1402 shall be provided for the chassis fuel system. The hose shall have a working temperature rating of -55 degree F to 300 degree F.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The ends of the hose shall have connections that shall allow the hose to be reattached if removed.

Fuel/Water Separator

A Racor fuel/water separator shall be installed in place of the Cummins fuel/water separator with drain. The unit shall utilize a three-step separate process: centrifuge for primary contaminant separation, conical baffles for water coalescing, and a replaceable filter for final particulate removal. The separator shall have a bottom drain for removing contaminants, shall be heated and shall have a rated maximum flow of 3.16 GPM. A sensor with indicator light and audible alarm shall be provided for the Racor fuel/water separator. The indicator light shall be mounted in the cab visible to the driver with the unit located inside the frame rails. The unit will alert the driver of high water content in the separator bowl.

320 Amp Alternator

There shall be a 320 amp Leece Neville alternator installed as specified. The alternator shall be a Leece Neville 4890JB series brushless type with integral rectifier and adjustable voltage regulator with an output of 272 amps per NFPA 1901 rating (320 amps per SAE J56).

Battery System

The manufacturer shall supply four (4) heavy duty Group 31 12-volt maintenance-free batteries. Each battery shall be installed and positioned so as to allow easy replacement of any single battery. Each battery shall be equipped with carrying handles to facilitate ease of removal and replacement. There shall be two (2) steel frame mounted battery boxes, one (1) on the left frame rail and one (1) on the right frame rail. Each battery box shall be secured to the frame rail with Grade 8 hardware. Each battery box shall hold (2) batteries. The batteries shall have a minimum combined rating of 4,000 (4 x 1000) cold cranking amps (CCA) @ 0 degrees Fahrenheit and 820 (4 x 205) minutes of reserve capacity for extended operation. The batteries shall have 3/8-16 threaded stud terminals to ensure tight cable connections. The battery stud terminals shall each be treated with concentrated industrial soft-seal after cable installation to promote corrosion prevention. The positive and negative battery stud terminals and the respective cables shall be clearly marked to ensure quick and mistake-proof identification.

Batteries shall be placed on non-corrosive rubber matting and secured with hold-down brackets to prevent movement, vibration, and road shock. The hold-down bracket J-hooks shall be cut to fit and shall have all sharp edges removed. The batteries shall be placed in plastic trays to provide preliminary containment should there be leakage of hazardous battery fluids. There shall be two (2) plastic trays, each containing (2) batteries. Each battery tray shall be equipped with a rubber vent hose to facilitate drainage. The rubber vent hose shall be routed to drain beneath the battery box. The batteries shall be positioned in well-ventilated areas.

One (1) positive and one (1) negative jumper stud shall be provided.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Batteries shall have a warranty of twelve (12) months that shall commence upon the date of delivery of the apparatus.

Engine Fan Clutch

The engine shall be equipped with a thermostatically controlled engine cooling fan. The fan shall be belt driven and utilize a clutch to engage when the engine reaches a specified temperature and / or the water pump is engaged (if equipped).

When disengaged, the fan clutch shall allow for improved performance from optional floor heaters, reduced cab interior noise, increased acceleration and improved fuel economy.

The fan shall be equipped with a fail-safe engagement so that if the clutch fails the fan shall engage to prevent engine overheating.

Drivelines

Drivelines shall have a heavy duty metal tube and shall be equipped with Spicer 1710HD universal joints to allow full-transmitted torque to the axle(s). Drive shafts shall be axially straight, concentric with axis and dynamically balanced.

Front Tow Eyes

Two (2) 3/4" thick heavy duty steel tow eyes shall be securely attached to the chassis frame rails at the front of the apparatus. They shall be mounted down below the bumper / cab.

Rear Tow Eyes

Two (2) heavy duty tow eyes made of 3/4" (0.75") thick steel having 2-1/2" diameter holes shall be mounted below the body at the rear of the vehicle to allow towing (not lifting) of the apparatus without damage. The tow eyes will be welded to the lower end of a 5" steel channel that is bolted at the end of the chassis frame rails. The tow eyes shall be painted chassis black.

Automatic Chassis Lubrication

A Vogel Automatic Lubrication System shall be installed to provide automatic grease application, with recommended dosages, per system interval cycle, to the following lubrication wear points:

- Spring Pins and Spring Hanger Pins @ 0.6 CCM
- King Pins, Upper and Lower @ 0.4 CCM
- Steering Linkage @ 0.2 CCM
- Tie Rod Ends @ 0.2 CCM
- Brake S-Cams @ 0.1 CCM (Rockwell will not warrant application to caliper slide pins)
- Steering Assist Cylinder (If applicable) @ 0.2 CCM

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

- Automatic Slack Adjusters @ 0.1 CCM
- Tilt Cab Lift Assembly (If applicable) @ 0.05 CCM

The lubrication system shall utilize the post lubrication principle and shall be powered by an electrically driven, 12V gear pump. The gear pump shall be top mounted to a reservoir assembly with a capacity of 2.716 lbs. grease liters. The electronic control unit shall be connected through the ignition and park brake circuits to provide power to the pump when the engine is running and the park brake is released.

The gear pump and reservoir shall be located in an accessible location.

The electronic control module shall include system monitoring capabilities for the main line and operating cycle with an indicator light visible from the driver's seat. The control module shall have LED's and a system reset button to initiate a lube cycle for diagnostic purposes and/or reset the control module in the event a system fault has occurred. Upon a fault, the system shall be inoperable until the fault has been corrected and a system reset has been initiated by the operator or serviceman.

On-Spot Tire Chains

The chassis shall be provided with On-Spot automatic tire chain system. The system shall include:

- An air cylinder containing one diaphragm, one return spring, one pushrod and a collapsible dust boot held in place with an Oetiker® style retainer to prevent foreign material from entering the air cylinder. The cylinder will be assembled with a two-piece cylinder clamp. The air cylinder will be cast aluminum and the lid will be threaded to receive a 90-degree DOT approved air fitting. The cylinder and lid must be anodized for corrosion resistance. Each cylinder will have 6 strengthening ribs. The cylinder wall thickness will be a minimum of 6mm.
- An extension rod and ball joint assembly that is fastened to the cylinder pushrod by means of a left hand thread. The ball joint must have a provision for greasings.
- A swing arm that is connected to the ball joint assembly with a nylock lock nut on one side and is fastened to the cylinder bracket at the pivot point. The arm will be supported by 2 greaseable arm bushings. The arm will be one-piece hardened alloy material that is formed in such a fashion that it allows the chainwheel to contact the vehicle tire at 3-1/2 to 4 inches off the ground.
- A chainwheel that is fastened to the arm with one 20mm bolt that is hardened to Metric Grade 8.8 along with a hardened lock nut. The bolt will also come with one chainwheel spacer for wheel height adjustment. The chainwheel will be 7-3/4 inches in diameter and will be constructed of a one-piece cast aluminum center hub that contains two maintenance-free sealed bearings. The circumference of the chainwheel will be rubber coated so that it may ride on the inside of the vehicle tire without causing any damage to the tire. There will be 6 lengths of chains approximately 13 inches long that will be welded to a single steel ring at 60-degree intervals. The steel ring will be bolted to the center hub with 6 Grade 8 cap screws and locknuts. Each length of chain will contain up

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

to 10 twisted links that are square-cut to provide for maximum traction in forward and reverse. Each chainwheel will be delivered with a chainwheel helmet to protect the chainwheel bearing and casting.

A switch shall be provided in the cab for activation of the tire chains.

DEF Tank

A diesel exhaust fluid (DEF) tank with a five (5) gallon capacity shall be provided.

The DEF tank shall include a heater fed by hot water directly from the engine block to prevent the DEF from becoming too cool to operate correctly per EPA requirements. The tank shall include a temperature sensor to control the heater control valve that controls the feed of hot water from the engine to the DEF tank heater.

A sender shall be provided in the DEF tank connected to a level gauge on the cab dash.

The tank shall be located left side below rear of cab.

Power Steering Cooler

A heat exchanger (cooler) shall be installed to maintain desired power steering fluid temperature. The cooler shall be a model DH-073-1-1 with air / oil design rated at 6300 BTU/HR @ 10 GPM. The cooler shall be mounted in front of the radiator and plumbed with #10 lines.

Long Cab

The vehicle shall be distinguished by an all-welded aluminum and fully enclosed tilt cab. The cab shall be designed exclusively for fire/rescue service and shall be pre-engineered to ensure long life. It shall incorporate an integral welded substructure of high-strength aluminum alloy extrusions that creates an occupant compartment that is essentially a protective perimeter. The end result is a distinctive structure that is aesthetically appealing, functionally durable, and characterized by increased personnel safety.

The cab shall be constructed from 3/16" (0.188") 3003 H14 aluminum alloy plate roof, floor, and outer skins welded to a high-strength 6063-T6 aluminum alloy extruded subframe. Wall supports and roof bows are 6061 T6 aluminum alloy. This combination of a high-strength, welded aluminum inner structure surrounded on all sides by load-bearing, welded aluminum outer skins provides a cab that is strong, lightweight, corrosion-resistant, and durable.

The inner structure shall be designed to create an interlocking internal "roll-cage" effect by welding two (2) 3" x 3" x 0.188" wall-thickness 6063-T5 aluminum upright extrusions between the 3" x 3" x 0.375" wall-thickness 6061-T6 roof crossbeam and the 2.25" x 3" x 0.435" wall-thickness 6063-T6 subframe structure in the front. An additional two (2) aluminum upright

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

extrusions within the back-of-cab structure shall be welded between the rear roof perimeter extrusion and the subframe structure in the rear to complete the interlocking framework. The four (4) upright extrusions -- two (2) in the front and two (2) in the rear -- shall be designed to effectively transmit roof loads downward into the subframe structure to help protect the occupant compartment from crushing in a serious accident. All joints shall be electrically seam welded internally using aluminum alloy welding wire.

The subframe structure shall be constructed from high-strength 6061-T6 aluminum extrusions welded together to provide a structural base for the cab. It shall include a side-to-side 3" x 1.5" .375 thick C-channel extrusion across the front, with 3/4" x 2-3/4" (.75" x 2.75") full-width crossmember tubes spaced at critical points between the front and rear of the cab.

The cab floor shall be constructed from 3/16" (0.188") 3003 H14 smooth aluminum plate welded to the subframe structure to give the cab additional strength and to help protect the occupants from penetration by road debris and under-ride collision impacts.

The cab roof shall be constructed from 3/16" (0.188") 3003 H14 aluminum treadplate supported by a grid of fore-aft and side-to-side aluminum extrusions to help protect the occupants from penetration by falling debris and downward-projecting objects. Molded fiberglass or other molded fiber-reinforced plastic roof materials are not acceptable.

The cab roof perimeter shall be constructed from 4" x 6-5/8" (4" x 6.625") 6063-T5 aluminum extrusions with integral drip rails. Cast aluminum corner joints shall be welded to the aluminum roof perimeter extrusions to ensure structural integrity. The roof perimeter shall be continuously welded to the cab roof plate to ensure a leak-free roof structure.

The cab rear skin shall be constructed from 3/16" (0.188") 3003 H14 aluminum plate. Structural extrusions shall be used to reinforce the rear wall.

The left-hand and right-hand cab side skins shall be constructed from 3/16" (0.188") 3003 H14 smooth aluminum plate. The skins shall be welded to structural aluminum extrusions at the top, bottom, and sides for additional reinforcement.

The cab front skins shall be constructed from 3/16" (0.188") 3003 H14 smooth aluminum plate. The upper portion shall form the windshield mask, and the lower portion shall form the cab front. Each front corner shall have a full 9" outer radius for strength and appearance. The left-hand and right-hand sides of the windshield mask shall be welded to the left-hand and right-hand front door frames, and the upper edge of the windshield mask shall be welded to the cab roof perimeter extrusion for reinforcement. The cab front shall be welded to the subframe C-channel extrusion below the line of the headlights to provide protection against frontal impact.

Cab Exterior

The exterior of the cab shall be 94" wide x 139.5" long to allow sufficient room in the occupant compartment for up to ten (10) fire fighters. The cab roof shall be approximately 101" above the

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

ground with the flat roof option. The back-of-cab to front axle length shall be a minimum of 67.5”.

Front axle fenderette trim shall be brushed aluminum for appearance and corrosion resistance. Bolt-in front wheelwell liners shall be constructed of 3/16” (0.188”) composite material to provide a maintenance-free, damage-resistant surface that helps protect the underside of the cab structure and components from stones and road debris.

The cab windshield shall be of a two-piece replaceable design for lowered cost of repair. The windshield shall be made from 1/4” (0.25”) thick curved, laminated safety glass with a 75% light transmittance automotive tint. A combined minimum viewing area of 2,700-sq. in. shall be provided. Forward visibility to the ground for the average (50th percentile) male sitting in the driver’s seat shall be no more than 11 feet 7 inches from the front of the cab to ensure good visibility in congested areas.

Cab Mounts and Cab Tilt System

The cab shall be independently mounted from the body and chassis to isolate the cab structure from stresses caused by chassis twisting and body movements. Mounting points shall consist of two (2) forward-pivoting points, one (1) on each side; two (2) intermediate rubber load-bearing cushions located midway along the length of the cab, one on each side; and two (2) combination rubber shock mounts and cab latches located at the rear of the cab, one (1) on each side.

An electric-over-hydraulic cab tilt system shall be provided to provide easy access to the engine. It shall consist of two (2) large-diameter, telescoping, hydraulic lift cylinders, one (1) on each side of the cab, with a frame-mounted electric-over-hydraulic pump for cylinder actuation.

Safety flow fuses (velocity fuses) shall be provided in the hydraulic lift cylinders to prevent the raised cab from suddenly dropping in case of a burst hydraulic hose or other hydraulic failure. The safety flow fuses shall operate when the cab is in any position, not just the fully raised position.

The hydraulic pump shall have a manual override system as a backup in the event of an electrical failure. Lift controls shall be located in a compartment to the rear of the cab on the right side of the apparatus. A parking brake interlock shall be provided as a safety feature to prevent the cab from being tilted unless the parking break is set.

The entire cab shall be tilted through a 42-45 degree arc to allow for easy maintenance of the engine, transmission and engine components. A positive-engagement safety latch shall be provided to lock the cab in the full tilt position to provide additional safety for personnel working under the raised cab.

In the lowered position, the cab shall be locked down by two (2) automatic, spring-loaded cab latches at the rear of the cab. A ”cab ajar” indicator light shall be provided on the instrument panel to warn the driver when the cab is not completely locked into the lowered position.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Cab Interior

The interior of the cab shall be of the open design with an ergonomically-designed driver area that provides ready access to all controls as well as a clear view of critical instrumentation.

The engine cover between the driver and the officer shall be a low-rise contoured design to provide sufficient seating and elbow room for the driver and the officer. The engine cover shall blend in smoothly with the interior dash and flooring of the cab. An all-aluminum subframe shall be provided for the engine cover for strength. The overall height of the engine enclosure shall not exceed 23" from the floor at each side and 27" in the center section. The engine cover shall not exceed 41" in width at its widest point.

The rear portion of the engine cover shall be provided with a lift-up section to provide easy access for checking transmission fluid, power steering fluid, and engine oil without raising the cab. The engine cover insulation shall consist of 3/4" dual density fiberglass composite panels with foil backing manufactured to specifically fit the engine cover without modification to eliminate "sagging" as found with foam insulation. The insulation shall meet or exceed DOT standard MVSS 302-1 and V-0 (UI subject 94 Test).

All cab floors shall be covered with a black rubber floor mat that provides an aggressive slip-resistant surface in accordance with current NFPA 1901.

A minimum of 57.25" of floor-to-ceiling height shall be provided in the front seating area of the cab and a minimum of 55.25" floor-to-ceiling height shall be provided in the rear seating area. A minimum of 36" of seated headroom at the "H" point shall be provided over each fenderwell.

The interior side to side dimensions shall be 87" from wall padding to wall padding and 89.5" from door to door.

The floor area in front of the front seat pedestals shall be no less than 24" side to side by up to 25.0" front to rear for the driver and no less than 24" side to side by up to 27.0" front to rear for the officer to provide adequate legroom.

The rear engine cover area shall be covered with molded 18 lb/cu. ft. (+/-0.5) flexible integral skinned polyurethane foam at a Durometer of 60 (+/- 5.0) per ASTM F1957-99. The cover shall be approximately .5" thick with a minimum skin thickness of 0.0625 inches. The cover shall be provided to reduce the transmission of noise and heat from the engine. The cover shall be black with a pebble grain finish for slip resistance.

Battery jumper studs shall be provided to allow jump-starting of the apparatus without having to tilt the cab.

All exposed interior metal surfaces shall be pretreated using a corrosion prevention system.

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

The interior of the cab shall be insulated to ensure the sound (dbA) level for the cab interior is within the limits stated in the current edition of NFPA 1901. The insulation shall consist of 2 oz. wadding and 1/4" (0.25") foam padding. The padding board shall be backed with 1/4" (0.25") thick reflective insulation. The backing shall be spun-woven polyester. Interior cab padding shall consist of a rear cab headliner, a rear wall panel, and side panels between the front and rear cab doors.

The vehicle shall use a seven-position tilt and telescopic steering column to accommodate various size operators. An 18" padded steering wheel with a center horn button shall be provided.

Storage areas, with hinged access doors, shall be provided below the driver and officer seats. The driver side compartment shall be approximately 19.25" x 17.75" x 5.75" high and the officer side compartment shall be approximately 18.25" x 22.5" x 11" high (19.25" x 17.75" x 5.75" w/ air ride).

The front cab steps shall be a minimum of 8" deep x 24" wide. The first step shall be no more than 24.0" above the ground with standard tires in the unloaded condition per NFPA 1901 standards. The rear cab steps shall be a minimum 12" deep x 21" wide. The first step shall be no more than 24.0" above the ground with standard tires in the unloaded condition per NFPA 1901 standards. The rear steps shall incorporate intermediate steps for easy access to the cab. The steps are to be located inside the doorsill, where they are protected against mud, snow, ice, and weather. The step surfaces shall be aluminum diamond plate with a multi-directional, aggressive gripping surface incorporated into the aluminum diamond plate in accordance with current NFPA 1901.

A black grip handle shall be provided on the interior of each front door below the door window to ensure proper hand holds while entering and exiting the cab. An additional black grip handle shall be provided on the left and right side windshield post for additional handholds.

Cab Doors

There shall be reflective signs on each cab door in compliance with all NFPA requirements.

Four (4) barrier style side-opening cab doors shall be provided. Doors shall be constructed of a 3/16" (0.188") aluminum plate outer material with an aluminum extruded inner framework to provide a structure that is as strong as the side skins.

Front cab door openings shall be approximately 36" wide x 71.5" high, and the rear cab door openings shall be approximately 33.75" wide x 73" high. The front doors shall open approximately 75 degrees, and the rear doors shall open approximately 80 degrees.

The doors shall be securely fastened to the doorframes with full-length, stainless steel piano hinges, with 3/8" (0.375") diameter pins for proper door alignment, long life, and corrosion resistance. Mounting hardware shall be treated with corrosion-resistant material prior to

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

installation. For effective sealing, an extruded rubber gasket shall be provided around the entire perimeter of all doors.

Stainless steel paddle-style door latches shall be provided on the interiors of the doors. The latches shall be designed and installed to protect against accidental or inadvertent opening as required by NFPA 1901.

The front door windows shall provide a minimum viewing area of 530 sq. in. each. The rear door windows shall provide a minimum viewing area of 500 sq. in. each. All windows shall have 75% light transmittance automotive safety tint. Full roll-down windows shall be provided for the front cab doors with worm gear drive cable operation for positive operation and long life. Scissors or gear-and-sector drives are not acceptable.

Cab Instruments and Controls

Two (2) pantograph-style windshield wipers with two (2) separate electric motors shall be provided for positive operation. Air-operated windshield wipers are not acceptable because of their tendency to accumulate moisture, which can lead to corrosion or to freezing in cold weather. The wipers shall be a wet-arm type with a one (1) gallon washer fluid reservoir, an intermittent-wipe function, and an integral wash circuit. Wiper arm length shall be approximately 28", and the blade length approximately 20". Each arm shall have a 70 degree sweep for full coverage of the windshield.

Cab controls shall be located on the cab instrument panel in the dashboard on the driver's side where they are clearly visible and easily reachable. Emergency warning light switches shall be installed in removable panels for ease of service. The following gauges and/or controls shall be provided:

- Master battery switch/ignition switch (rocker with integral indicator)
- Starter switch/engine stop switch (rocker)
- Heater and defroster controls with illumination
- Marker light/headlight control switch with dimmer switch
- Self-canceling turn signal control with indicators
- Windshield wiper switch with intermittent control and washer control
- Master warning light switch
- Transmission oil temperature gauge
- Air filter restriction indicator
- Pump shift control with green "pump in gear" and "o.k. to pump" indicator lights
- Parking brake controls with red indicator light on dash
- Automatic transmission shift console
- Electric horn button at center of steering wheel
- Cab ajar warning light on the message center enunciator

Controls and switches shall be identified as to their function by backlit wording adjacent to each switch, or indirect panel lighting adjacent to the controls.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Fast Idle System

A fast idle system shall be provided and controlled by the cab-mounted switch. The system shall increase engine idle speed to a preset RPM for increased alternator output.

Electrical System

The cab and chassis system shall have a centrally located electrical distribution area. All electrical components shall be located such that standard operations shall not interfere with or disrupt vehicle operation. An automatic thermal-reset master circuit breaker compatible with the alternator size shall be provided. Automatic-reset circuit breakers shall be used for directional lights, cab heater, battery power, ignition, and other circuits. An access cover shall be provided for maintenance access to the electrical distribution area.

A 6 place, constantly hot, and 6 place ignition switched fuse panel and ground for customer-installed radios and chargers shall be provided at the electrical distribution area. Radio suppression shall be sufficient to allow radio equipment operation without interference.

All wiring shall be mounted in the chassis frame and protected from impact, abrasion, water, ice, and heat sources. The wiring shall be color-coded and functionally-labeled every 3" on the outer surface of the insulation for ease of identification and maintenance. The wiring harness shall conform to SAE 1127 with GXL temperature properties. Any wiring connections exposed to the outside environment shall be weather-resistant. All harnesses shall be covered in a loom that is rated at 280 degrees F to protect the wiring against heat and abrasion.

A Vehicle Data Computer (VDC) shall be supplied within the electrical system to process and distribute engine and transmission Electronic Control Module (ECM) information to chassis system gauges, the message center, and related pump panel gauges. Communication between the VDC and chassis system gauges shall be through a 4 wire multiplexed communication system to ensure accurate engine and transmission data is provided at the cab dash and pump. The VDC shall be protected against corrosion, excessive heat, vibration, and physical damage.

Two (2) dual rectangular chrome plated headlight bezels shall be installed on the front of the cab. The low beam headlights shall activate with the release of the parking brake to provide daytime running lights (DRL) for additional vehicle conspicuity and safety. The headlight switch shall automatically override the DRL for normal low beam/high beam operation.

Cab Crashworthiness Requirement

The apparatus cab shall meet and/or exceed relevant NFPA 1901 load and impact tests required for compliance certification with the following:

Side Impact Dynamic Pre-Load per SAE J2422 (Section 5).

KINGSTON FIRE DISTRICT SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Testing shall meet and/or exceed defined test using 13,000 ft-lbs of force as a requirement. The cab shall be subject to a side impact representing the force seen in a roll-over. The cab shall exhibit minimal to no intrusion into the cab's occupant survival space, doors shall remain closed and cab shall remain attached to frame.

Cab testing shall be completed using 13,776 ft-lbs of force **exceeding** testing requirements.

Quasi-static Roof Strength (proof loads) per SAE J2422 (Section 6) / ECE R29, Annex 3, paragraph 5.

Testing shall meet and/or exceed defined test using 22,046 lbs of mass as a requirement. Testing shall be completed using platen(s) distributed uniformly over all bearing members of the cab roof structure.

Cab testing shall be completed using 23,561 lbs of mass **exceeding** testing requirements. The cab shall exhibit minimal to no intrusion into the cab's occupant survival space and doors shall remain closed.

Additional cab testing shall be conducted using 117,336 lbs of mass **exceeding** testing requirements by **over five (5) times**. The cab shall exhibit minimal to no intrusion into the cab's occupant survival space and the doors shall remain closed.

Frontal Impact per SAE J2420.

Testing shall meet and/or exceed defined test using 32,549 ft-lbs of force as a requirement. The cab shall be subject to a frontal impact as defined by the standard. The cab shall exhibit minimal to no intrusion into the cab's occupant survival space, doors shall remain closed and cab shall remain attached to frame.

Cab testing shall be completed using 34,844 ft-lbs of force **exceeding** testing requirements.

Additional cab testing shall be conducted using 65,891 ft-lbs of force **exceeding** testing requirements by **over two (2) times**.

A copy of a certificate or letter verifying compliance to the above performance by an independent, licensed, professional engineer shall be provided upon request.

For any or all of the above tests, the cab manufacturer shall provide either photographs or video footage of the procedure upon request.

Seat Mounting Strength

The cab seat mounting surfaces shall be third party tested and in compliance with FMVSS 571.207.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Seat Belt Anchor Strength

The cab seat belt mounting points shall be third party tested and in compliance with FMVSS 571.210.

ISO Compliance

The manufacturer shall ensure that the construction of the apparatus cab shall be in conformance with the established ISO-compliant quality system. All written quality procedures and other procedures referenced within the pages of the manufacturer's Quality Manual, as well as all Work Instructions, Workmanship Standards, and Calibration Administration that directly or indirectly impacts this process shall be strictly adhered to. By virtue of its ISO compliance the manufacturer shall provide an apparatus cab that is built to exacting standards, meets the customer's expectations, and satisfies the customer's requirements.

Raised Roof

The rear portion of the cab roof shall be raised 12". This will provide at least 5` 7" standing room. The front of the vista hood shall be sloped at 45 degrees from the vertical. The slope shall begin slightly in front of the centerline of the front axle to leave room for warning lights and air conditioning in front of the vista. The main roof extrusion shall extend up into the vista to strengthen the roof perimeter. Windows shall be provided on front, side, and rear unless otherwise specified.

The rear door shall have an 85" vertical dimension for improved ingress/egress characteristics.

Cab Grille

The front cooling air intake grille shall be constructed of stainless steel mesh and supported by a 0.80" polished stainless steel frame providing no less than 81% open area for excellent cooling performance.

Rear Cab Door Position

The cab rear doors shall be moved to the rear of the wheel opening. This door placement facilitates easier entry and egress by reducing the rear facing seat protrusion into the door opening.

Rear door position to the 58" or (medium cab).

Cab Front Door Windows

Driver and officer door windows shall have the support pillar located toward the front of the window. There shall be a vent that can be opened and closed within the window itself, located towards the front.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Cab Door Locks

Each cab door shall have a manual operated door lock actuated from the interior of each respective door. Exterior of each cab door shall be provided with a barrel style keyed lock below the cab door handle.

Cab Door Locks

The cab shall have 1250 keyed door locks provided on exterior doors to secure the apparatus.

Cab Door Front Windows

Driver and Officer door windows. Includes electric roll-down actuation. Each door to have individual control at door position and the driver door is to have master control for all power window locations.

Cab Door Rear Windows

Rear crew cab door windows. Includes electric roll-down actuation. Each door to have individual control. Not available with paddle style door latching.

Cab Door Panels

The inner door panels shall be made from 14 gauge brushed finish stainless steel for increased durability. The cab door panels shall incorporate an easily removable panel for access to the latching mechanism for maintenance or service.

Cab Door Exterior Latches

All cab doors shall have "L" style exterior door latches.

Cab Door Stainless Steel Trim

Each cab door shall have a stainless steel trim on the trailing edge of the door opening. Rear doors shall have full vertical height trim; front cab doors shall be 50" tall on rear vertical edge above floor level.

Cab Door Handle Scuff Plates

A stainless steel scuff plate shall be installed at all cab door "L" handles for added paint protection.

Cab Door Area Lighting

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

There shall be four (4) clear LED lights provided to illuminate the cab step well area. Each light shall be located on each cab door in the inboard position. Each light shall be activated by the cab door ajar circuit.

Cab Door Reflective Material

Reflective Red/Fluorescent Yellow Green 3M Diamond Grade material striping shall be supplied on each of the cab doors. The stripes shall run from the lower outer corner to the upper inside corner of the panel, forming an "A" shape when viewed from the rear. The material shall meet NFPA 1901 requirements for size (96 square inches) and reflectivity.

Mirror Extension

There shall be a 2” extension provided for each Ramco mirror.

Cab Mirrors

Two (2) Ramco model 6001FFR remote controlled aluminum mirrors shall be installed. The mirrors shall incorporate a full face main section with a convex mirror with housing model CAS750, mounted to the top. The adjustment of main sections shall be through dash mounted switches. Location: mounted on front corners of cab.

Cab Windows Rear Wall

Fixed glass windows shall be supplied on either side of the cab, providing visibility at the rear. The windows shall be approximately 4” wide and approximately the same height as the door windows.

Cab Canopy Window

There shall be a fixed window provided between the front and rear doors on the driver and officer`s side of the cab.

Front Mudflaps

Black linear low density polyethylene (proprietary blend) mudflaps shall be installed on the rear of the cab front wheelwells. The design of the mudflaps shall have corrugated ridges to distribute water evenly.

Handrails

Cab door assist handrails shall consist of two (2) 1.25” diameter x 18” long 6063-T5 anodized aluminum tubes mounted directly behind the driver and officer door openings one each side of the cab. The handrails shall be machine extruded with integral ribbed surfaces to assure a good

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

grip for personnel safety. Handrails shall be installed between chrome end stanchions and shall be positioned at least 2" from the mounting surface to allow a positive grip with a gloved hand.

Handrails

Cab door assist handrails shall consist of two (2) 1.25" diameter x 36" long 6063-T5 anodized aluminum tubes mounted directly behind the driver and officer rear door openings one each side of the cab. The handrails shall be machine extruded with integral ribbed surfaces to assure a good grip for personnel safety. Handrails shall be installed between chrome end stanchions and shall be positioned at least 2" from the mounting surface to allow a positive grip with a gloved hand.

Rear Cab Wall Construction

The rear cab wall shall be constructed using formed 3/16" aluminum smooth plate interlocking in aluminum extrusions. The smooth plate shall match the cab paint scheme.

Receptacle Mounting Plate

A mounting plate shall be provided for the battery charger receptacle, battery charger indicator and if applicable the air inlet, etc. The plate shall be constructed of 14 gauge brushed finish stainless steel and be removable for service access to the receptacle(s) and indicator.

Air Conditioning

An overhead air-conditioner / heater system with a single radiator mounted condenser shall be supplied.

The unit shall be mounted to the cab interior headliner in a mid-cab position, away from all seating positions. The unit shall provide ten (10) comfort discharge louvers, four (4) to the back area of the cab and six (6) to the front. These louvers will be used for AC and heat air delivery. Two (2) additional large front louvers shall be damper controlled to provide defogging and defrosting capabilities to the front windshield as necessary.

The unit shall consist of a high output evaporator coil and heater core with one (1) high output dual blower for front air delivery, and two (2) high performance single wheel blowers for rear air delivery.

The control panel shall actuate the air-distribution system with air cylinders, which are to be separated from the brake system by an 85-90 psi pressure protection valve. A three-speed blower switch shall control air speed.

The condenser shall be radiator mounted and have a minimum capacity of 65,000 BTU's and shall include a receiver drier.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Performance Data: (Unit only, no ducting or louvers)

- AC BTU: 55,000
- Heat BTU: 65,000
- CFM: 1300 @ 13.8V (All blowers)

The compressor shall be a ten-cylinder swash plate type Seltec model TM-31HD with a capacity of 19.1 cu. in. per revolution.

The system shall be capable of cooling the interior of the cab from 100 degrees ambient to 75 degrees or less with 50% relative humidity in 30 minutes or less.

HVAC Control Location

Heating and air conditioning controls shall be located in the center dash area.

Cab Seats

All cab seats shall be Bostrom brand.

Cab Seating

One (1) H. O. Bostrom 400 Series Sierra Air- 100RX4 suspension seats with high back styling shall be supplied for the driver position.

Features shall include:

- Air-100 suspension assembly with weight, height and ride adjustment.
- Built in lumbar support.
- 4" vertical suspension motion.
- 5" fore and aft adjustment.

One (1) H. O. Bostrom 400 Series fixed seat with high back SCBA storage for the officer's position shall be supplied.

Features shall include:

- Removable "Store-All" side cushions.
- Auto-pivot and return headrest to open for improved exit with SCBA.
- 12.5" wide SCBA cavity to store leading SCBA Brands.
- Built in lumbar support.
- Replaceable seat, side and headrest cushions.

One (1) Bostrom 400 Series tanker 450 SCBA high back SCBA storage seat shall be provided in the rear facing position over the driver side wheelwell.

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

Features shall include:

- Removable "Store-All" side cushions.
- Auto-pivot and return headrest to open for improved exit with SCBA.
- 12.5" wide SCBA cavity to store leading SCBA Brands.
- Built in lumbar support.
- Replaceable seat, side and headrest cushions.

One (1) Bostrom 400 Series tanker 450 SCBA high back SCBA storage seats shall be provided in the rear facing position over the officer side wheelwell.

Features shall include:

- Removable "Store-All" side cushions.
- Auto-pivot and return headrest to open for improved exit with SCBA.
- 12.5" wide SCBA cavity to store leading SCBA Brands.
- Built in lumbar support.
- Replaceable seat, side and headrest cushions.

Two (2) H. O. Bostrom 400 Series fixed seats with high back SCBA storage shall be provided on the center of the rear wall in the center position. The seats shall be mounted on a common seat riser.

Features shall include:

- Removable "Store-All" side cushions.
- Auto-pivot and return headrest to open for improved exit with SCBA.
- 12.5" wide SCBA cavity to store leading SCBA Brands.
- Built in lumbar support.
- Replaceable seat, side and headrest cushions.

All seat positions shall have a bright red retractable 3-point lap and shoulder harness, providing additional safety and security for personnel. Extensions shall be provided with the seat belts so the male end can be easily grasped and the female end easily located while sitting in a normal position.

Seat Fabric Color

All seats shall be gray in color.

Seating Capacity Tag

A tag that is in view of the driver stating seating capacity of six (6) personnel shall be provided.

Bostrom SecureAll Locking System

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

The H.O. Bostrom SecureAll™ SCBA Locking System shall be one bracket model and store all U.S. and international SCBA brands and sizes while in transit or for storage on fire trucks. The bracket shall be easily adjustable; all adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the tank in-place for a safe and comfortable fit in seat cavity. Firefighters shall simply push the SCBA unit against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ bracket shall fit in all H.O. Bostrom Tanker SCBA seats including ABTS and non-ABTS seats and all flip-up ABTS and non-ABTS seats. Additional seat depth shall not be required for proper bracket fit; changes to the shroud back shall not be required for proper mounting of the bracket.

The standard release handle shall be integrated into the seat cushion for quick and easy release and shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The H.O. Bostrom SecureAll™ system meets NFPA 1901 standards and requirements of EN 1846-2.

The bracket(s) shall be located officer's seat, rear facing driver's side, inboard driver's side rear wall, inboard officer's side rear wall, rear facing officer's side.

Seat Belt Extender

ReadyReach seat belt extenders shall be provided. The extender shall include an arm that places the shoulder belt D-loop in a closer, easier to reach location.

The extenders shall be provided for the driver's seat, officer's seat, rear facing driver's side, inboard driver's side rear wall, inboard officer's side rear wall, rear facing officer's side seat.

Seat Cover Material

Seat cover low seam Durawear Plus (EA). Bostrom seats on bottom cushion only.

Medical Cabinet

A medical cabinet shall be provided for the vista area rearward of the rear cab doors. The cabinet shall be constructed of 1/8" (.125) smooth aluminum and shall include three (3) horizontally hinged lift-up doors. The cabinet shall be approximately 88" wide x vista height. Depth will be approximately 10" on a long cab with medium length doors and 22" on an extended cab with medium length doors. The compartment openings shall be approximately 12" wide (outboard) and 50" (center). The interior of the cabinet shall be open from left to right side.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Medical Storage Cabinet Finish

The medical storage cabinet(s) shall have a Zolatone gray finish. The finish shall be applied to the interior, exterior, shelves (if equipped) and trays (if equipped) of the cabinet.

Rear Engine Cover Storage Box

An aluminum map/storage box shall be installed in the cab. The map box shall be constructed of 1/8" (.125) smooth aluminum with three (3) individual compartments. One (1) compartment shall be located on the forward area of the map box with an angled top with no dividers. The dividers shall be able to adjust from side to side. The remaining two (2) compartments shall be located on the rear of the box, one (1) with a top opening and one (1) low on the rear face of the box.

Hinged covers, with push button latches, shall be provided for each compartment. The latches shall have a 25 lb. rating.

The map box shall be mounted in the cab area centered on top of the rear engine cover. The map box shall be secured and tested to meet with current N.F.P.A. requirements.

Approximate Dimensions:

24" high x 22" wide x 28" long (with ISM engine).

26" high x 22" wide x 27" long (with S60 engine).

27" high x 22" wide x 27" long (with Quest Cab only).

Map Box Finish

The map box(es) shall have Zolatone gray #20-64 finish.

Cab Interior Color

Cab instrument panel, overhead console, trim panels, headliner, and door panels shall be gray.

Sun Visors

Lexan sun visors shall be provided for the driver and officer matching the interior trim of the cab and shall be flush mounted into the underside of the overhead console.

Air Horn Lanyard

There shall be a "Y" style lanyard mounted in the center of the cab that allows the driver and officer to operate the air horns. The lanyard shall activate an electrical air switch.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Engine Cover

The engine cover shall blend in smoothly with the interior dash and flooring of the cab. The upper left and right sides shall have a sloped transition surface running front to rear providing increased space for the driver and officer.

The engine cover and engine service access door cover shall be molded 18 lb/cu. ft. (+/-0.5) flexible integral skinned polyurethane foam at a Durometer of 60 (+/- 5.0) per ASTM F1957-99. The cover shall be approximately .5" thick with a minimum skin thickness of 0.0625 inches. The cover shall be provided to reduce the transmission of noise and heat from the engine. The cover shall be black and feature a pebble grain finish for slip resistance.

Cup Holder / Storage Tray

A cup holder and tray assembly shall be provided on the cab engine cover between the driver and officer. The tray shall be approximately 14" wide x 10" long x 1.5" tall and constructed from .125" aluminum plate. The top edge of the tray sides shall have a .5" lip and the front corners of the tray shall be tapered for dash access. The two (2) cup holders shall be constructed from 3.5" diameter pipe approximately 2.5" tall and be located one each side at the rear corners of the tray. The assembly shall be painted to match the cab interior color.

Cab Dash - Severe Duty

The center and officer side dash shall be constructed from .125" smooth aluminum plate painted to match the cab interior. The officer side dash panel shall be lowered to provide increased visibility. A hinged access panel shall be provided on top of the center dash to provide easy access to components within.

The lower kick panels below the dash to be constructed from .125" aluminum smooth plate painted to match cab interior. The panels shall be removable to allow for servicing components that may be located behind the panels.

Overhead Console

A severe duty forward overhead console, air conditioning plenum and rear facing blower cover shall be provided. Each overhead console section shall be constructed of aluminum smooth plate painted to match the cab interior. The console shall be installed using stainless steel fasteners.

Severe Duty Driver Dash

The driver side upper dash shall be provided constructed of smooth aluminum painted to match the cab interior. The upper gauge package shall be provided with an ABS housing only.

Rear Engine Cover

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The rear engine cover shall be provided with a reduced profile for increased legroom on the forward facing rear inboard seats.

Cab Door Warning Lights

One (1) Whelen model PSR00FRR LED red flashing strip light shall be provided on each interior cab door panel. The lights shall be horizontal mounted on the lower kick panels and wired through the door switch.

Cab Dome Lights

Five (5) ceiling mounted dome light assemblies shall be provided.

Each light shall consist of a three-position assembly mounted rocker switch, LED (light emitting diode) 4" grommet mount white dome light, LED (light emitting diode) 4" grommet mount red dome light, and a plastic housing.

The red light activates with appropriate cab door and light assembly mounted rocker switch. The white light activates with assembly mounted rocker switch only.

Two (2) lights shall be located in the front of the cab and three (3) lights shall be located in the rear of the cab.

Radio

The apparatus cab shall be equipped with a Delphi model PP105713 heavy duty AM/FM/Weather band stereo receiver. The unit shall include a compact disc player, front auxiliary input and front USB port.

Two (2) 5-1/4" radio speakers and antenna shall be supplied and mounted in the padding adjacent to driver and officer seats.

The receiver unit shall be suppressed from engine noise to provide clear sound through the speakers.

Location: center overhead.

Radio Speakers Additional Pair

An additional pair of radio speakers shall be supplied.

Rear speakers mounted in rear headliner. Speakers shall be 5-1/4" diameter.

Clamshell Switch

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

A heavy duty metal clamshell switch shall be installed on the officer`s side of the engine cover to operate the Q2B.

Horn Button Switch

A two (2) position rocker switch shall be installed in the cab accessible to the driver and properly labeled to enable operator to activate the OEM traffic horn or air horn from the steering wheel horn button.

Battery Charger Receptacle

A 20 amp battery charger receptacle shall be installed in the specified location.

The receptacle shall be located outside driver's door next to handrail.

The cover color shall be Red.

Auto Transfer Switch

An automatic transfer switch shall be installed to allow all interior receptacles to be powered either by the shore power receptacle or the on-board generator.

The system shall include an eight (8) place breaker box for the interior receptacles.

ATC Override

An Automatic Traction Control (ATC) override switch shall be provided. The switch shall be located within reach of the driver and allow for momentary disabling of the ATC system due to mud or snow conditions.

English Dominant Gauge Cluster

The cab operational instruments shall be located in the dashboard on the driver side of the cab and shall be clearly visible. The gauges in this panel shall be English dominant and shall be the following:

- Speedometer/Odometer
- Tachometer with integral hour meter
- Engine oil pressure gauge with warning light and buzzer
- Engine water temperature gauge with warning light and buzzer
- Two (2) air pressure gauges with a warning light and buzzer (front air and rear air)
- Fuel gauge
- Voltmeter
- Transmission oil temperature gauge

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

This panel shall be backlit for increased visibility during day and night time operations.

Headlights

The front of the cab shall have four (4) headlights. The headlights shall be mounted on the front of the cab in the lower position. The headlights shall be day time operational.

Battery Charger/Air Compressor

A Kussmaul Auto-Charge 1200 battery charger and air compressor with automatic battery charger shall be installed.

The battery charger shall be completely automatic with an output of 0-40 amps @ 12 volts DC and an input current requirement of 10 amps @ 120 volts AC.

A Kussmaul air compressor with automatic battery conditioner model 091-9-1200 shall be installed. The battery conditioner is completely automatic with a 0-40 amp output to maintain the charge in the battery system. The air compressor shall be powered by a 12 volt DC output from the battery charger and has an output of .30 cfm at 80 PSI. A pressure switch senses the system pressure and operates the compressor whenever the pressure in the air brake system drops below a pre-determined level.

12 Volt Outlets (2)

A plug-in type receptacle for hand held spotlights, cell phones, chargers, etc. shall be installed in cab officer side on 3 x 3 post rear facing just above engine cover and officer's side dash. The receptacles shall be wired battery hot.

Antenna Bases (4)

There shall be a Tessco P/N 90942 universal antenna base mounted on the cab roof with a weatherproof connector. The antenna base shall be NMO Motorola Style (equivalent to a MATM style) with RG58U coax cable. The antenna shall be located driver side forward with coaxial cable terminating at the center of the dash board, officer side forward with coaxial cable terminating at the center of the dash board, officer side rearward with coaxial cable terminating at the center of the dash board, and drive side rearward with coaxial cable terminating at the center of the dash board.

Battery Charger Location

The battery charger shall be located behind driver's seat.

Air Compressor Location

The air compressor shall be located behind driver's seat.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Cab Turn Signals

There shall be a pair of Whelen M6 LED (Light Emitting Diode) turn signal light heads with populated arrow pattern and amber lens mounted upper headlight bezel and wired with weatherproof connectors.

Cab USB Charging Port

A dual USB charging port for cell phones, chargers, etc. shall be installed officer side dash. The receptacles shall be wired battery hot.

DPF Regeneration Override

A momentary override switch shall be provided for the Diesel Particulate Filter (DPF) regeneration. The switch will inhibit the regeneration process until the switch is reset or the engine is shut down and restarted. The switch shall be located within reach of the driver.

LED Cab Headlights

Peterson LED headlights shall be provided. LED lights shall be provided in the low and high beam position of the head lamp assembly.

Driver Side Assembly

The driver side assembly shall be constructed entirely of aluminum extrusions and interlocking aluminum plates. This aluminum modular design shall provide a high strength-to-weight ratio for increased equipment carrying capacity.

The driver side body corners shall be 6063-T5 extruded aluminum corner sections with a 3/16" (0.188") wall thickness. The side body extrusions shall be 6063-T5 aluminum tubing with a 3/16" (0.188") wall thickness and 3/16" (0.188") outside corner radius. The corners and sides shall be welded both internally and externally at each joint using an aluminum alloy welding wire.

The driver side body shall be completely sanded and deburred to assure a smooth finish and painted job color.

Driver Side Compartments

The three (3) driver side compartments shall be constructed from 3003 H14 1/8" (.125") smooth aluminum plate. The compartments shall be modular in design and shall not be a part of the body support structure.

There shall be one (1) compartment located ahead of the rear wheels. This compartment shall be approximately 42" wide x 68" high x 26" deep in the lower 30" high section and 12" deep in the

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

upper 38" high section. The compartment shall contain approximately 30 cu. ft. of combined storage space. The door opening shall be approximately 42" wide x 68" high.

There shall be one (1) compartment located over the rear wheel. The compartment shall be approximately 56" wide x 34" high x 12" deep and contain approximately 13.2 cu. ft. of storage space. The door opening shall be approximately 56" wide x 34" high.

There shall be one (1) compartment located behind of the rear wheels. This compartment shall be approximately 56" wide x 68" high x 26" deep in the lower 30" high section and 12" deep in the upper 38" high section. The compartment shall contain approximately 40 cu. ft. of combined storage space. The door opening shall be approximately 56" wide x 68" high.

Each compartment seam shall be sealed using a permanent pliable silicone caulk. The walls of each compartment shall be machine-louvered for adequate ventilation.

An externally-mounted compartment top shall be provided and constructed of a 1/8" (.125") aluminum treadplate.

Driver Side Roof Top Compartments

Driver side roof compartment shall be provided. The compartment shall be constructed of 1/8" (.125") aluminum treadplate.

The compartment shall have vertical hinged access door at the rear constructed of 1/8" (.125") smooth plate aluminum painted job color. The access door shall include push button latch and be wired to the door ajar indicator in the cab.

Lighting shall be provided for the compartment. The light(s) shall illuminate when the access door is in the open position.

Officer Side Assembly

The officer side assembly shall be constructed entirely of aluminum extrusions and interlocking aluminum plates. This aluminum modular design shall provide a high strength-to-weight ratio for increased equipment carrying capacity.

The officer side body corners shall be 6063-T5 extruded aluminum corner sections with a 3/16" (0.188") wall thickness. The side body extrusions shall be 6063-T5 aluminum tubing with a 3/16" (0.188") wall thickness and 3/16" (0.188") outside corner radius. The corners and sides shall be welded both internally and externally at each joint using an aluminum alloy welding wire.

The officer side body shall be completely sanded and deburred to assure a smooth finish and painted job color.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Officer Side Compartments

The three (3) officer side compartments shall be constructed from 3003 H14 1/8" (.125") smooth aluminum plate. The compartments shall be modular in design and shall not be a part of the body support structure.

There shall be one (1) compartment located ahead of the rear wheels. This compartment shall be approximately 42" wide x 68" high x 26" deep in the lower 30" high section and 12" deep in the upper 38" high section. The compartment shall contain approximately 30 cu. ft. of combined storage space. The door opening shall be approximately 42" wide x 68" high.

There shall be one (1) compartment located over the rear wheel. The compartment shall be approximately 56" wide x 34" high x 12" deep and contain approximately 13.2 cu. ft. of storage space. The door opening shall be approximately 56" wide x 34" high.

There shall be one (1) compartment located behind of the rear wheels. This compartment shall be approximately 56" wide x 68" high x 26" deep in the lower 30" high section and 12" deep in the upper 38" high section. The compartment shall contain approximately 40 cu. ft. of combined storage space. The door opening shall be approximately 56" wide x 68" high.

Each compartment seam shall be sealed using a permanent pliable silicone caulk. The walls of each compartment shall be machine-louvered for adequate ventilation.

An externally-mounted compartment top shall be provided and constructed of a 1/8" (.125") aluminum treadplate.

Ladder Rack

A 2-arm overhead ladder rack shall be provided to place the ladders at a safe and convenient height for unloading and loading. The rack shall be located over the body.

The rack shall utilize two (2) hydraulic rotary actuators, one (1) located inside the front compartment and one (1) located inside the rear compartment. The rack shall utilize two (2) lifting arms which are located outside of both the front and rear compartments. The lifting arms shall be made of 6061-T6 aluminum with a wall thickness of 0.60". The rack shall have a main mounting rack for attaching ladders and accessories. The main mounting rack shall be made of 6061-T6 aluminum extrusion with a wall thickness of 0.25" and end plates made of 0.75" thick 6061-T6 aluminum.

The rack shall be electrical/hydraulic operated by a durable high cycle 12 volt actuator and controlled by the multiplex electrical system by means of a control panel. The ladder rack control panel shall include a master on/off switch, a lifting arm raise/lower switch, a power indicator light and an operating instruction plate. The control panel shall be mounted on the pump panel adjacent to the ladder rack of the apparatus to allow the operator to monitor operations and

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

ground personnel while lowering and raising the rack. The assembly shall have appropriate safety labeling.

The rack shall be capable of raising and lowering a maximum of seven hundred (700) pounds of dry load equipment from chest height at ground level to the storage position above the hosebed. The ladder brackets shall use low friction wear pads for protection. The rack shall be easily configurable for mounting various complements of ladders, pike poles, hard suction hoses, etc.

A visual signal shall be provided to indicate when the ladder rack is not in the stowed position by two (2) amber flashing lights, one (1) on each end of the rack. The rack shall also be wired through the door ajar indicator light located in the cab to alert the driver that the rack is not stowed if the park brake is released. Two (2) safety locks, one (1) for each lifting arm, shall be provided to automatically secure the lifting arms while in the travel/stowed position. Reflective material shall be applied to the outboard side of the lifting arms.

The ladder rack assembly shall meet requirements of NFPA 1901.

Officer Side Roof Top Compartments

Officer side roof compartment shall be provided. The compartment shall be constructed of 1/8" (.125") aluminum treadplate.

The compartment shall have vertical hinged access door at the rear constructed of 1/8" (.125") smooth plate aluminum painted job color. The access door shall include push button latch and be wired to the door ajar indicator in the cab.

Lighting shall be provided for the compartment. The light(s) shall illuminate when the access door is in the open position.

Roof Top Compartment Contents

Officer and driver side roof top compartment shall each hold (1) 10' length of hard suction hose (not included). Includes stop bracket rearward of hard suction hose and Nylatron compartment flooring.

Rear Body Compartment

The rear body shall be constructed entirely of aluminum extrusions and interlocking aluminum plates and includes a lower full height center rear compartment.

The rear body frame shall be 6063-T5 1.5" x 4" and 1.5" x 3" aluminum extrusions with a 3/16" (0.188") wall thickness and 3/16" (0.188") outside corner radius and 1/8" (0.125") aluminum plate. The rear extrusions shall be welded both internal and external at each joint using an aluminum alloy welding wire.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Rear Body Compartment

The rear compartment shall be constructed from 3003 H14 1/8" (.125") smooth aluminum plate. The compartment shall be modular in design and shall not be a part of the body support structure.

The compartment shall be approximately 38" wide x 30" high and as deep as applicable to required tank design per application. The door opening shall be approximately 38" wide x 30" high. This compartment shall be transverse through to the side rear compartments.

The compartment seams shall be sealed using a permanent pliable silicone caulk. Machined louvers shall be provided for adequate ventilation.

Tailboard

Tailboard Step

A tailboard step shall be provided at the rear of the body. The tailboard shall 14" in depth and in accordance with NFPA in both step height and stepping surface. The maximum rear step height to the tailboard shall not exceed 24".

The tailboard step shall be formed from 3/16" (0.188") aluminum treadplate and shall be reinforced with 6063-T5 1.5" x 3" aluminum extrusion. The tailboard shall be in accordance with current NFPA requirements and shall include a multi-directional aggressive gripping surface incorporated into the diamond plate. The gripping surface shall protrude from the diamond plate sheet a minimum of 1/8" (0.125"). Gripping surfaces shall be circular in design, a minimum of 1" diameter and on centers not to exceed 4".

The tailboard step shall be bolted on to the body from the underside assuring a clear surface and shall be easily removable for replacement in the case of damage.

Rear Access Handrails

Handrails shall be provided at the rear of the body to assist ground personnel accessing the tailboard step and hosebed area. Each handrail shall be constructed of 6063T5 1.25" OD anodized aluminum tube, with an integral ribbed surface to assure a good grip for personnel safety, and shall be mounted between chrome stanchions.

The handrails shall be located- two (2) handrails, one (1) on each side, appropriately sized handrail mounted vertical on the trailing edge of the body and appropriately sized handrail(s) mounted horizontal below the rear hosebed opening.

Single Compartment Doors

A single compartment door shall be constructed using a box pan configuration. The outer door pan shall beveled and shall be constructed from 3/16" (0.188") aluminum plate. The inner door

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

pan shall be constructed from 3/32" (0.090") smooth aluminum plate and shall have nutsert fittings to attach hold-open hardware. The inner pan shall have a 95-degree bend to form an integral drip rail.

The compartment door shall have a 1" x 9/16" (1" x 0.43") closed-cell "P" EPDM sponge gasket meeting ASTM D-1066 2A4 standards installed around the perimeter of the door to provide a seal that is resistant to oil, sunlight, and ozone.

A drain hole shall be installed in the lower corner of the inside door pan to assist with drainage.

A polished stainless steel Hansen D-ring style twist-lock door handle with a #459 latch shall be provided on the door. The 4-1/2" (4.5") D-ring handle shall be mounted directly to the door latching mechanism with screws that do not penetrate the door material for improved corrosion resistance.

The compartment door shall be securely attached to the apparatus body with a full-length stainless steel 1/4" (0.25") rod piano-type hinge isolated from the body and compartment door with a dielectric barrier. The door shall be attached with machine screws threaded into the doorframe. The door shall have gas shock-style hold-open devices.

An anodized aluminum drip rail shall be mounted over the compartment opening to assist in directing water runoff away from the compartment.

The door(s) shall be installed in the following location(s): L2, R2

Double Compartment Doors

Double compartment doors shall be constructed using a box pan configuration. The outer door pans shall beveled and shall be constructed from 3/16" (0.188") aluminum plate. The inner door pans shall be constructed from 3/32" (0.090") smooth aluminum plate and shall have nutsert fittings to attach hold-open hardware. The inner pans shall have a 95-degree bend to form an integral drip rail.

The compartment doors shall have a 1" x 9/16" (1" x 0.43") closed-cell "P" EPDM sponge gasket meeting ASTM D-1066 2A4 standards installed around the perimeter of the doors to provide a seal that is resistant to oil, sunlight, and ozone.

A drain hole shall be installed in the lower corner of the inside door pan to assist with drainage.

A polished stainless steel Hansen D-ring style twist-lock door handle with a #459 latch shall be provided on the primary door. The 4-1/2" (4.5") D-ring handle shall be mounted directly to the door latching mechanism with screws that do not penetrate the door material for improved corrosion resistance.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The secondary door shall have a dual stage rotary latch with a 750 lb rating to hold the door in the closed position. The latch shall be mounted at the top of the door. A stainless steel paddle style handle shall be mounted on the interior pan of the door to actuate the rotary latch. The paddle handle shall be connected to the rotary latch by a 5/32" (.156") diameter rod. Cable actuation shall be deemed un-acceptable due to the potential for cable stretch and slippage. The striker pin shall be 3/8" (.38") diameter with slotted mounting holes for adjustment.

Double door latch to have latch brackets fabricated from .125 aluminum smooth plate, installed with "PULL" tags #1032993 for left side and #1032294 for right side.

The compartment doors shall be securely attached to the apparatus body with a full-length stainless steel 1/4" (0.25") rod piano-type hinge isolated from the body and compartment doors with a dielectric barrier. The doors shall be attached with machine screws threaded into the doorframe.

The doors shall have a gas shock-style hold-open device. The gas shocks shall have a 30 lb rating and be mounted near the top of the door (when possible).

An anodized aluminum drip rail shall be mounted over the compartment opening to assist in directing water runoff away from the compartment.

The door(s) shall be installed in the following location(s): B1

Double Compartment Doors

Double compartment doors shall be constructed using a box pan configuration. The outer door pans shall beveled and shall be constructed from 3/16" (0.188") aluminum plate. The inner door pans shall be constructed from 3/32" (0.090") smooth aluminum plate and shall have nutsert fittings to attach hold-open hardware. The inner pans shall have a 95-degree bend to form an integral drip rail.

The compartment doors shall have a 1" x 9/16" (1" x 0.43") closed-cell "P" EPDM sponge gasket meeting ASTM D-1066 2A4 standards installed around the perimeter of the doors to provide a seal that is resistant to oil, sunlight, and ozone.

A drain hole shall be installed in the lower corner of the inside door pan to assist with drainage.

A polished stainless steel Hansen D-ring style twist-lock door handle with a #459 latch shall be provided on the primary door. The 4-1/2" (4.5") D-ring handle shall be mounted directly to the door latching mechanism with screws that do not penetrate the door material for improved corrosion resistance.

The secondary door shall have two (2) dual stage rotary latches, each with a 750 lb rating to hold the door in the closed position. The latches shall be mounted at the top and bottom of the door. A stainless steel paddle style handle shall be mounted on the interior pan of the door to actuate the

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

rotary latches. The paddle handle shall be connected to the rotary latches by 5/32" (.156") diameter rods. Cable actuation shall not be deemed un-acceptable due to the potential for cable stretch and slippage. The striker pins shall be 3/8" (.38") diameter with slotted mounting holes for adjustment.

Double door latch to have latch brackets fabricated from .125 aluminum smooth plate, installed with "PULL" tags #1032993 for left side and #1032294 for right side.

The compartment doors shall be securely attached to the apparatus body with a full-length stainless steel 1/4" (0.25") rod piano-type hinge isolated from the body and compartment doors with a dielectric barrier. The doors shall be attached with machine screws threaded into the doorframe.

The doors shall have a gas shock-style hold-open device. The gas shocks shall have a 30 lb rating and be mounted near the top of the door (when possible).

An anodized aluminum drip rail shall be mounted over the compartment opening to assist in directing water runoff away from the compartment.

The door(s) shall be installed in the following location(s): L1, L3, R1, R3

Rear Hosebed Cover

A cover constructed of heavy duty black nylon cargo netting shall be installed at the rear apparatus hosebed.

The bottom of the cargo netting shall be mechanically attached to the hosebed. The cover shall be attached to comply with the latest edition of NFPA 1901.

Cover shall secure the hoseload at the rear open back of the hosebed and shall compliment separate top cover of vinyl, diamond plate or similar cover that secures top of body open areas over hoseload.

Vinyl Crosslay Cover

A cover constructed of Black 18 oz. PVC vinyl coated polyester shall be installed on the crosslay. The base fabric shall be 1000 x 1300 Denier Polyester with a fabric count of 20 x 20 per square inch.

The cover shall be held in place across the top of the body by chrome snaps. The sides of the cover shall have integral flaps that extend down to cover the sides of the crosslay. The side flaps shall be secured in place to comply with the latest edition of NFPA 1901.

Hosebed Cover

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The hosebed area shall have a two (2) piece aluminum hosebed cover. The hosebed cover shall be provided in compliance with NFPA.

Each hosebed cover shall be constructed of an aluminum frame with a 1/8" (.125") embossed aluminum tread plate top.

The rear section shall slide over the forward section on tracks and rollers. The two sections shall then lift upward on a forward mounted stainless steel piano hinge to assist in loading hose. The lid shall be assisted and supported by gas shocks and also have prop-rod style set up as a locking mechanism in open position. The roller section shall also consist of positive latch open and close.

Each cover door shall be wired to the door ajar indicator light in the cab and shall be interlocked with the parking brake per NFPA.

Requires intermediate rear step except for extended enhanced compartments.

Pump Module

Pump Module Frame

An extruded aluminum pump module shall be provided and located forward of the apparatus body. The pump module shall be constructed entirely of welded aluminum alloy extrusions and interlocking aluminum plates. The pump module framework shall consist of 1.5" x 3" x .188" wall, 1.5" x 3" x .375" wall with center web and 3" x 3" x .188" wall extrusions.

The pump module design and mounting shall be separate from the body to allow the pump module and body to move independently of each other in order to reduce stress from frame twisting and vibration.

The exterior surface of the pump module framework shall have a sanded finish.

Pump Module Mounting

The pump module shall be attached to the chassis using four (4) center bonded isolation mounts and a steel mounting frame. The isolation mounts shall be 2.75" diameter and mount to the chassis with two (2) 4" x 4" x .312" A36 steel angles.

Pump Access

A pump service access door shall be provided at the front of the pump module. The door shall be secured with two (2) thumb latches. (Access door not provided on fixed cab applications)

Pump Module Running Boards

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

The pump module shall include a running board on each side. The running boards shall be in accordance with NFPA in both step height and stepping surface. The running boards shall be formed from .125" aluminum treadplate.

Stepping Surface

Each running board shall include a multi-directional, aggressive gripping surface incorporated into the treadplate. The surface shall extend vertically from the diamond plate sheet a minimum of .125". Gripping

surfaces shall be circular in design, a minimum of 1" diameter and on centers not to exceed 4". Each running board shall be bolted on to the pump module and be easily removable for replacement in the case of damage.

Side Mount Pump Panels

The driver and officer side pump panels shall be constructed of 14 gauge stainless steel. Each panel shall have the ability to be removed from the module for easier access and for maintenance in the pump area.

Pump Access Door

The officer side pump module shall include an upper horizontal hinged pump access door.

The door shall be constructed of 14 gauge brushed stainless steel. The compartment door shall be securely attached with a full-length stainless steel piano type hinge with 1/4" pins. The hinge shall be "staked" on every other knuckle to prevent the pin from sliding. The door shall include two (2) push-button style latches to secure the door in the closed position and two (2) hold-open devices to hold the door in the open position.

Pump Panel Tags

Color coded pump panel labels shall be supplied to be in accordance with NFPA 1901 compliance.

Flex Joint

The area between the pump modules and body shall include a rubber flex joint.

Air Horn Switch

A heavy duty weatherproof push-button switch shall be installed at the pump operator's panel to operate the air horns.

The switch shall be labeled "Evacuation Alert".

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Location: driver side pump panel.

Storage Pan

A storage pan shall be provided in the upper pump module area. The pan shall be constructed of 3/16" (.188") aluminum treadplate and be removable to service items in the pump module below. Holes shall be provided in the corners of the pan to facilitate drainage of water.

Single Crosslay Hosebed

One (1) crosslay hosebed shall be provided on the pump module. The crosslay area shall have a capacity for 300 to 400` of 2.5" double-jacket fire hose double stacked. The crosslay floor and side walls shall be constructed of 3/16" (.188) smooth aluminum plate. The floor shall be slotted to prevent the accumulation of water and allow for ventilation of wet hose.

Transverse Storage Compartment

A compartment shall be provided for storage of (1) Alco-lite CJL-10 above the pump panel area. The storage area is to be fully enclosed with a vertical hinged diamond plate access door hinged rearward provided at each side for easy access from both sides of the apparatus. The doors shall be equipped with glove box style latches. The opening is to be 8" wide.

780 Gallon Water Tank

A 780 gallon (U.S.) "L" booster tank shall be supplied.

The booster tank shall be constructed of polypropylene material. The booster tank shall be completely removable without disturbing or dismounting the apparatus body structure. The top of the booster tank is fitted with removable lifting assembly designed to facilitate tank removal.

The booster tank top, sides, and bottom shall be constructed of a minimum 1/2" (0.50") thick black UV-stabilized copolymer polypropylene. Joints and seams shall be fused using nitrogen gas as required and tested for maximum strength and integrity. The tank construction shall include technology wherein a sealant shall be installed between the plastic components prior to being fusion welded. This sealing method will provide a liquid barrier offering leak protection in the event of a weld compromise. The tank cover shall be constructed of 1/2" thick polypropylene and UV stabilized, to incorporate a multi-piece locking design, which allows for individual removal and inspection if necessary. The tank cover(s) shall be flush or recessed 3/8" from the top of the tank and shall be fused to the tank walls and longitudinal partitions for maximum integrity. Each one of the covers shall have hold downs consisting of 2" minimum polypropylene dowels spaced a maximum of 40" apart. These dowels shall extend through the covers and will assist in keeping the covers rigid under fast filling conditions.

The tank shall have a combination vent and manual fill tower with a hinged lid. The fill tower shall be constructed of 1/2" polypropylene and shall be a typical dimension of 8" x 8" outer

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

perimeter (subject to change for specific design applications). The fill tower shall be blue in color indicating that it is a water-only fill tower. The tower shall have a 1/4" thick removable polypropylene screen and a polypropylene hinged cover. The capacity of the tank shall be engraved on the top of the fill tower lid.

The booster tank shall have two (2) tank plumbing openings. One (1) for a tank-to-pump suction line with an anti-swirl plate, and one (1) for a tank fill line. All tank fill couplings shall be backed with flow deflectors to break up the stream of water entering the tank, and be capable of withstanding sustained fill rates per the tank fill inlet size.

The sump shall be constructed of a minimum of 1/2" polypropylene. The sump shall have a minimum 3" N.P.T. threaded outlet for a drain plug per NFPA. This shall be used as a combination clean-out and drain. All tanks shall have an anti-swirl plate located approximately 3" above the inside floor.

The transverse and longitudinal swash partitions shall be manufactured of a minimum of 3/8" polypropylene. All partitions shall be equipped with vent and air holes to permit movement of air and water between compartments. The partitions shall be designed to provide maximum water flow. All swash partitions interlock with one another and are completely fused to each other as well as to the walls of the tank. All partitions and spacing shall comply with NFPA 1901. The walls shall be welded to the floor of the tank providing maximum strength.

Inside the fill tower there shall be a combination vent/overflow pipe. The vent overflow shall be a minimum of schedule 40 polypropylene pipe with an I.D. of 3" or larger that is designed to run through the tank. This outlet shall direct the draining of overflow water past the rear axle, thus reducing the possibility of freeze-up of these components in cold environments. This drain configuration shall also assure that rear axle tire traction shall not be affected when moving forward.

The booster tank shall undergo extensive testing prior to installation in the truck. All water tanks shall be tested and certified as to capacity on a calibrated and certified tilting scale.

Each tank shall be weighed empty and full to provide precise fluid capacity. Each tank shall be delivered with a Certificate of Capacity delineating the weight empty and full and the resultant capacity based on weight. Engineering estimates for capacity calculations shall not be permitted for capacity certification. The tank must be designed and fabricated by a tank manufacturer that is ISO 9001:2008 certified in each of its locations. The ISO certification must be to the current standard in effect at the time of the design and fabrication of the tank.

A tag shall be installed on the apparatus in a convenient location and contain pertinent information including a QR code readable by commercially available smart phones. The information contained on the tag shall include the capacity of the water and foam (s), the maximum fill and pressure rates, the serial number of the tank, the date of manufacture, the tank manufacturer, and contact information. The QR code will allow the user to connect with the tank manufacturer for additional information and assistance.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The tank shall have a limited Lifetime warranty that provides warranty service for the life of the fire apparatus in which the tank is installed. Warranties are transferable if the apparatus ownership changes by requesting the transfer from the tank manufacturer.

Tank capacity is 780 US gallon / 649 Imperial gallons / 2952 Liters.

Tank Fill

One (1) 2” pump-to-tank fill line having a 2” manually operated full flow valve. The valve control shall be located at the pump operator`s panel and shall visually indicate the position of the valve at all times. The fill line shall be controlled using a chrome handle with an integral tag.

The valve shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position with water flowing through it.

The valve shall be of unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance and decreased friction loss.

Tank to Pump

One (1) manually operated 3” Akron valve shall be installed between the pump suction and the booster tank. Includes flex hose with stainless steel hose clamps for connection to the 4” tank sump outlet . The valve control shall be located at the pump operator`s panel and shall visually indicate the position of the valve at all times.

The valve shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position and water is flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance and decreased friction loss.

A check valve shall be provided in the tank to pump supply line to prevent the possibility of "back filling" the water tank. The valve control shall be located at the pump operator`s panel and shall visually indicate the position of the valve at all times.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Ladder Rack Finish

The 2-arm ladder rack shall have a sanded finish.

Ladder Storage

Attic Ladder Storage Brackets

Two (2) brackets shall be provided that shall be capable for the storage of one (1) attic ladder. The brackets shall be constructed of high tensile strength aluminum alloy and shall be located outboard side of ladder rack.

Pike Pole Storage

Two (2) aluminum tubes shall be mounted on the overhead ladder rack for storing of two (2) pike poles. The tubes shall be mounted on the outboard side of the rack.

Ladder Brand

The ladder brand capable of being carried on the unit shall be Duo-Safety.

Hydraulic Power Supply

Hydraulic Power Supply for E-ONE 2-arm ladder rack. Location: officer side of hosebed storage pan.

Required storage space for hydraulic power supply: 17" wide x 22" long x 12" deep.

Pike Pole

The pike pole(s) capable of being stored shall be the following length: (2) 10' pike poles.

Ladders

The length of ladders capable of being stored shall be the following: 28' 2-section and 16' roof ladder.

Storage Tube Retaining Pin

The storage tube(s) shall have a secondary retaining pin with cable. This retaining pin shall provide additional securing of the tube contents while the apparatus is in transit and on scene.

Intermediate Pump Panel Step

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

An intermediate pump panel step shall be provided.

The intermediate step shall be constructed of 3/16" (.187") aluminum treadplate. The step shall include a multi-directional, aggressive gripping surface incorporated into the treadplate. The surface shall extend vertically from the diamond plate sheet a minimum of 1/8" (.125"). Gripping surfaces shall be circular in design, a minimum of 1" diameter and on centers not to exceed 4". The step shall be bolted onto the pump module and be easily removable for replacement in the case of damage.

Lighting shall be provided to and positioned illumination of the upper surface of the step.

Intermediate Rear Step

An intermediate step shall be provided on the rear of the apparatus.

The step shall be constructed of 3/16" (.187") aluminum treadplate. The step shall include a multi-directional, aggressive gripping surface incorporated into the treadplate. The step shall be bolted to the rear end assembly and be easily removable for replacement in the case of damage.

One (1) handrail shall be installed in compliance with current NFPA. The handrails shall be constructed of 6063T5 1.25" OD anodized aluminum tube, with an integral ribbed surface to assure a good grip for personnel safety, mounted between chrome stanchions.

Hosebed Folding Steps

Innovative Controls dual lighted LED folding steps shall be positioned to the driver side rear of the body. The steps shall be NFPA compliant for access to the hosebed storage area and in step height and surface area. The steps shall be staggered stepped as applicable with tailboard depth, not applicable with recessed step mounting.

Innovative Controls dual lighted folding step with LED lights integral to the step on the top to provide NFPA requirements of 2 fc (20 lx) on the stepping surface. Folding step shall also have a LED light integral to the bottom of the step to meet NFPA requirements of a stepping surface up to 18" below the step. The folding step shall sustain a minimum static load of 500 lb with a 3 to 1 safety factor. The folding step shall also meet NFPA slip resistance qualifications. Corrosion resistance shall be demonstrated by a 1000 hr salt spray test with no visible signs of deterioration of the step body or hardware.

One (1) hand rail shall be installed (as applicable) in compliance with current NFPA. The hand rail shall be constructed of 6063T5 1.25" OD anodized aluminum tube, with an integral ribbed surface to assure a good grip for personnel safety, mounted between chrome stanchions.

Hosebed Folding Steps

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Innovative Controls dual lighted LED folding steps shall be positioned to the officer side rear of the body. The steps shall be NFPA compliant for access to the hosebed storage area and in step height and surface area. The steps shall be staggered stepped as applicable with tailboard depth, not applicable with recessed step mounting.

Innovative Controls dual lighted LED folding step with LED lights integral to the step on the top to provide NFPA requirements of 2 fc (20 lx) on the stepping surface. Folding step shall also have a LED light integral to the bottom of the step to meet NFPA requirements of a stepping surface up to 18" below the step. The folding step shall sustain a minimum static load of 500 lb with a 3 to 1 safety factor. The folding step shall also meet NFPA slip resistance qualifications. Corrosion resistance shall be demonstrated by a 1000 hr salt spray test with no visible signs of deterioration of the step body or hardware.

One (1) hand rail shall be installed (as applicable) in compliance with current NFPA. The hand rail shall be constructed of 6063T5 1.25" OD anodized aluminum tube, with an integral ribbed surface to assure a good grip for personnel safety, mounted between chrome stanchions.

Pump Panel Folding Steps

Innovative Controls dual lighted LED folding step(s) shall be located officer side front compartment face. The folding step(s) shall meet current NFPA in step height and surface area.

Innovative Controls dual lighted LED folding step with LED lights integral to the step on the top to provide NFPA requirements of 2 fc (20 lx) on the stepping surface. Folding step shall also have a LED light integral to the bottom of the step to meet NFPA requirements of a stepping surface up to 18" below the step. The folding step shall sustain a minimum static load of 500 lb with a 3 to 1 safety factor. The folding step shall also meet NFPA slip resistance qualifications. Corrosion resistance shall be demonstrated by a 1000 hr salt spray test with no visible signs of deterioration of the step body or hardware.

One (1) hand rail shall be installed in compliance with current NFPA. The hand rail shall be constructed of 6063T5 1.25" OD anodized aluminum tube, with an integral ribbed surface to assure a good grip for personnel safety, mounted between chrome stanchions.

Mudflaps

Black mudflaps with OEM logo shall be provided for the body wheelwells.

Hosebed

The area above the booster tank shall have a hose storage area provided. The hosebed shall be constructed entirely from maintenance-free, 3/4" deep x 7.5" wide, extruded aluminum slats that shall be pop-riveted into a one-piece grid system. Each slat shall have all sharp edges removed and have an anodized ribbed top surface that shall prevent the accumulation of water and allow for ventilation of wet hose.

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

The hosebed shall include an open area for the fill tower(s). The hosebed design shall incorporate adjustable tracks in the forward area rearward of the fill tower(s) and the rearward area of the hosebed for the installation of an adjustable divider(s). The adjustable tracks shall hold an adjustable divider(s) mounting nut straight, so only a Philips head screwdriver is required to adjust a divider(s) from side to side (as is practical with other hosebed mounted equipment).

The hosebed shall be easily removable to allow access to the booster tank below.

Hosebed Dividers (4)

There shall be a hosebed divider provided the full fore-aft length of the hosebed.

The hosebed divider shall be constructed of 1/4" (0.25") smooth aluminum plate with an extruded aluminum base welded to the bottom. The rear end of the divider shall have a 3" radius corner to protect personnel. The divider shall be natural finish aluminum for long-lasting appearance and shall be sanded and de-burred to prevent damage to the hose.

The divider shall be adjustable from side to side in the hosebed to accommodate varying hose loads.

Storage Pan

A storage pan shall be provided in the forward area of the hosebed.

The storage pan shall be constructed of 3/16" (.188") aluminum tread plate.

Hosebed Divider Hand Hold

There shall be a hand hole cut-out(s) on the trailing edge of each hosebed divider. The cut-out(s) is specifically sized for use in adjusting of the hosebed divider.

Divider Support

Divider Support shall run full width of hosebed (side to side) at the front of the hosebed and towards the rear of the hosebed at top of the divider(s). Attach to each hosebed divider to provide additional support.

Floor Matting

This unit shall have all applicable compartment floors, shelves, and trays covered with a heavy duty Dri-Dek brand Black floor matting.

Pac Trac

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Pac Trac shall be provided in the upper and lower area of each compartment back wall as specified.

Stainless Steel Trim

A stainless steel trim shall be located at the bottom edge of compartment L1, L2, L3, R1, R2, R3 opening. The trim shall provide added protection of the painted surface of the body when equipment is removed from the compartment.

Fuel Fill

A recessed fuel fill shall be provided at the driver side rear wheelwell area.

Fill Tower Location

The fill tower(s) shall be located inside the hosebed storage pan as applicable.

Body Wheelwell

The body wheelwell frame shall be constructed from 6063-T5 aluminum extrusion with a slot the full length to permit an internal fit of 1/8" (0.125") aluminum treadplate. The wheelwell trim fenderett shall be constructed from 6063-T5 formed aluminum extrusion. The wheelwell liners shall be constructed of a 3/16" (.187") composite material. The liners shall be bolt-on and shall provide a maintenance-free and damage-resistant surface.

Corner Guards

The forward body corners of the body shall have corner guards installed. The corner guards shall be constructed of (.063") aluminum treadplate.

Corner Guards

The rearward body corners of the body shall have corner guards installed. The corner guards shall be constructed of (.063") aluminum treadplate.

Rub Rail

The pump area module(s) and body shall have rub rails mounted along the sides and at the rear.

The rub rail shall be C-channel in design and constructed of 3/16" thick 6463T6 anodized aluminum extrusion. The rub rail shall be 2.75" high x 1.25" deep and shall extend beyond the body width to protect compartment doors and the body side. The rub rail depth shall allow marker and/or warning lights to be recessed inside for protection.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The top surface of the rub rail shall have minimum of five (5) raised serrations. Each serration being a minimum of .1" in height and with cross grooves to provide a slip-resistant edge for the tailboard step and pump module running board areas. The rub rail shall be mounted a minimum of 3/16" off the pump module and body with nylon spacers. The ends of each section shall be provided with a finished rounded corner piece.

Body Height and Mainframe Construction

The body mainframe shall be entirely constructed of aluminum. The complete framework shall be constructed of 6061T6 and 6063T5 aluminum alloy extrusions welded together using 5356 aluminum alloy welding wire.

The body mainframe shall include 3" x 3" 6061-T6 aluminum 3/8" (0.375") wall crossmember extrusion or 3" x 3" I-beam section aluminum extrusion depending on the application at the front of the body . A solid 3" x 3" "I-beam" section aluminum extrusion shall be provided the full width of the body forward and rearward of the rear wheelwell. The crossmembers shall be designed to support the compartment framing and shall be welded to 1-3/16" x 3" (1.188" x 3") solid 6063-T5 aluminum frame sill extrusions. The frame sill extrusions shall be shaped to contour with the chassis frame rails and shall be protected from contact with the chassis frame rails by 5/16" x 2" (0.31" x 2") fiber-reinforced rubber strips to prevent wear and galvanic corrosion caused when dissimilar metals come in contact.

Body Mounting System

The main body shall be attached to the chassis frame rails with six (6) of 5/8" (0.625") diameter steel U-bolts. This body mounting system shall be used to allow easy removal of the body for major repair or disassembly.

Water Tank Mounting System

The body design shall allow the booster tank to be completely removable without disturbing or dismounting the apparatus body structure. The water tank shall rest on top of a 3" x 3" frame assembly covered with rubber shock pads and corner braces formed from 3/16" angled plate to support the tank. The booster tank mounting system shall utilize a floating design to reduce stress from road travel and vibration. To maintain low vehicle center of gravity the water tank bottom shall be mounted within 5" of the frame rail top.

Hosebed Side Assembly

The hosebed side assemblies shall be made of 3" x 3" slotted aluminum extrusion and 3/16" (.188") smooth plate. The hosebed side assemblies shall provide an 88" high body.

The exterior hosebed side surface shall be completely sanded and deburred to assure a smooth finish and painted job color. The interior hosebed side surface shall be completely sanded and deburred to assure a smooth sanded finish.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

SCBA Straps

Straps shall be provided in each exterior storage compartment to provide secondary means to hold each SCBA bottle in the compartment. The straps shall be constructed from 1" nylon webbing formed in a loop. The strap(s) shall be mounted to the storage compartment ceiling directly inside the door opening at each bottle location.

SCBA Bottle Storage

Fire Shopp brand SCBA bottle storage with hinged door and push button latch shall be provided in the body wheelwell area for up to (5) spare bottles.

The door shall have a brushed stainless steel finish.

Wheel Chock Storage

A custom designed wheel chock storage with hinged door and push button latch shall be provided in the body wheelwell area.

The door shall match the wheelwell area material and finish.

The door shall be wired to "Door Open" indicator inside cab.

Pump Rating

The fire pump shall be rated at 1500 GPM.

Fire Pump System

The pump shall be a midship-mounted Hale QMAX single stage centrifugal pump. The pump shall be mounted on the chassis frame rails of commercial or custom truck chassis and have the capacity of 1,250 to 2,250 gallons per minute (U.S. GPM) NFPA 1901 rated performance, and shall be split-shaft driven from the truck transmission.

The entire pump body and related parts shall be of fine grain alloy cast iron, with a minimum tensile strength of 30,000 psi (207 MPa). All metal moving parts in contact with water shall be of high quality bronze or stainless steel. Pump body shall be horizontally split in two sections, for easy removal of impeller assembly including wear rings and bearings from beneath the pump without disturbing pump mounting or piping.

The pump impeller shall be hard, fine grain bronze of the mixed flow design and shall be individually ground and hand balanced. Impeller clearance rings shall be bronze, easily renewable without replacing impeller or pump volute body, and of wrap-around double labyrinth design for maximum efficiency.

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

The pump shaft shall be heat-treated, corrosion-resistant stainless steel and shall be rigidly supported by three (3) bearings for minimum deflection. The sleeve bearing is to be lubricated by a force fed, automatic oil lubricated design, pressure-balanced to exclude foreign material. The remaining bearings shall be heavy-duty, deep groove ball bearings in the gearbox and shall be splash-lubricated. Pump shaft must be sealed with double-lip oil seal to keep road dirt and water out of the gearbox.

Two (2) 6" diameter suction ports with 6" NST male threads and removable screens shall be provided, one each side. The ports shall be mounted one (1) on each side of the midship pump and shall extend through the side pump panels. Inlets shall come equipped with long handle chrome caps.

Discharge Manifold

The pump system shall utilize a stainless steel discharge manifold system that allows a direct flow of water to discharge valves. The manifold and fabricated piping systems shall be constructed of a minimum of Schedule 10 stainless steel to reduce corrosion.

Pump Shift

The pump shift shall be pneumatically-controlled using a power shifting cylinder.

The power shift control valve shall be mounted in the cab and be labeled "PUMP SHIFT". The apparatus transmission shift control shall be furnished with a positive lever, preventing accidental shifting of the chassis transmission.

A green indicator light shall be located in the cab and be labeled "PUMP ENGAGED". The light shall not activate until the pump shift has completed its full travel into pump engagement position.

A second green indicator light shall be located in the cab and be labeled "OK TO PUMP". This light shall be energized when both the pump shift has been completed and the chassis automatic transmission has obtained converter lock-up (4th gear lock-up).

Test Ports

Two (2) test plugs shall be pump panel mounted for third party testing of vacuum and pressures of the pump.

Gearbox Cooler

A gearbox cooler shall be provided to maintain safe operating temperatures during prolonged pumping operations for pump rating 1500 GPM and over.

Pump Certification

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The pump, when dry, shall be capable of taking suction and discharging water in accordance with current NFPA 1901. The pump shall be tested at the manufacturer's facility by an independent, third-party testing service. The conditions of the pump test shall be as outlined in current NFPA 1901.

The tests shall include, at a minimum, the pump test, the pumping engine overload test, the pressure control system test, the priming device tests, the vacuum test, and the water tank to pump flow test as outlined in current NFPA 1901.

A piping hydrostatic test shall be performed as outlined in current NFPA 1901.

The pump shall deliver the percentage of rated capacities at pressures indicated below:

- 100% of rated capacity at 150 psi net pump pressure
- 100% of rated capacity at 165 psi net pump pressure
- 70% of rated capacity at 200 psi net pump pressure
- 50% of rated capacity at 250 psi net pump pressure

A test plate, installed at the pump panel, shall provide the rated discharges and pressures together with the speed of the engine as determined by the certification test, and the no-load governed speed of the engine.

A Certificate of Inspection certifying performance of the pump and all related components shall be provided at time of delivery. Additional certification documents shall include, but not limited to, Certificate of Hydrostatic Test, Electrical System Performance Test, Manufacturer's Record of Pumper Construction, and Certificate of Pump Performance from the pump manufacturer.

Steamers

The pump 6" steamer intake(s) shall be mounted approximately 1" from the pump panel to back of cap when installed. The "Flush+1" dimension can vary + or - 1-1/4" or as practicable depending on the pump module width and options selected. (Example 72" or 76" modules.)

Location: driver's side, officer's side.

Zinc Anodes

The zinc anodes help prevent damage caused by galvanic corrosion within the fire pump. The system provides a sacrificial metal which helps to diminish or prevent pump and pump shaft galvanic corrosion. One anode will be located on the suction side and one will be located on the discharge side of the pump.

Thermal Relief Valve

A Hale TRVL-120 thermal relief valve shall be provided.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The valve shall help protect the pump by automatically monitoring pump water temperature. The relief valve shall automatically dump a controlled amount of water to the ground when the pump water exceeds the pre-set temperature of the relief valve.

A pump panel mounted indicator shall be installed at the pump operator`s panel.

Pump Seal Packing

The pump shaft shall have only one (1) packing gland located on the inlet side of the pump. It shall be of split design for ease of repacking. The packing gland shall be of a design to exert uniform pressure on packing and to prevent cocking and uneven packing load when tightened. The packing rings shall be permanently lubricated, graphite composition and have sacrificial zinc foil separators to protect the pump shaft from galvanic corrosion.

The packing shall be easily adjusted by hand with rod or screw driver with no special tools or wrenches required.

Master Drain Valve

A manual master drain valve shall be installed on the pump panel. The master pump drain assembly shall consist of a Class 1 bronze master drain with a rubber disc seal. The master drain shall have a rubber seal to prevent water from running out on the running board.

The manual master drain valve shall have twelve (12) individual-sealed ports that allow quick and simultaneous draining of multiple intake and discharge lines. It shall be constructed of corrosion-resistant material and be capable of operating at a pressure of up to 600 PSI.

The master drain shall provide independent ports for low point drainage of the fire pump and auxiliary devices.

Pump Cooler

The pump shall have a 3/8" line installed from the pump discharge to the booster tank to allow a small amount of water to circulate through the pump casing in order to cool the pump during sustained periods of pump operation when water is not being discharged. The pump cooler line shall be controlled from the pump operator`s panel by an Innovative Controls 1/4 turn valve with "T" handle. Each 1/4 turn handle grip shall feature built-in color-coding labels and a verbiage tag

Trident Primer

A Trident air operated priming system shall be installed. The unit shall be of all brass and stainless steel construction and designed for fire pumps of 1,250 GPM (4,600 LPM) or more. Due to corrosion exposure no aluminum or vanes shall be used in the primer design. The primer shall be three-barrel design with 3/4" NPT connection to the fire pump.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The primer shall be mounted above the pump impeller so that the priming line will automatically drain back to the pump. The primer shall also automatically drain when the panel control actuator is not in operation. The inlet side of the primer shall include a brass "wye" type strainer with removable stainless steel fine mesh strainer to prevent entry of debris into the primer body.

The system shall create vacuum by using air from the chassis air brake system through a two-barrel multi-stage internal "venturi nozzles" within the primer body. The noise level during operation of the primer shall not exceed 75 Db.

Air Flow Requirements

The primer shall require a minimum of 15.6 cubic foot per minute air compressor and shall be capable of meeting drafting requirements at high idle engine speed. The air supply shall be from a chassis supplied "protected" air storage tank with a pressure protection valve. The air supply line shall have a pressure protection valve set between 70 to 80 PSIG.

Primer Control

The primer control shall have a manually operated, panel mounted "push to prime" air valve. The valve shall direct air pressure from the air brake storage tank to the primer body. To prevent freezing, no water shall flow to and from the panel control.

Warranty

The primer shall be covered by a five (5) year parts warranty.

2.5" Left Intake

Two (2) 2-1/2" suction inlets with a manually operated 2-1/2" Akron valve shall be provided on the left side pump panel.

The valves shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position and water is flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

The outlet of the valve shall be connected to the suction side of the pump with the valve body located behind the pump panel. The valve shall come equipped with a brass inlet strainer, 2-1/2" NST female chrome inlet swivel, and shall be equipped with a chrome plated rockerlug plug with a retainer device.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The valve control shall be located at the pump operator's panel and shall visually indicate the position of the valve at all times.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance, and decreased friction loss.

A 3/4" bleeder valve assembly will be installed on the left side pump panel.

Front Intake

A 5" stainless steel pipe shall extend from the right intake side of the pump to the front of the apparatus. The intake shall be controlled by a 5" butterfly valve and shall be air operated and controlled from the operator's panel. A valve(s) shall be provided to allow water to be drained.

An adjustable pressure relief valve shall be provided. The pressure relief valve shall be factory set to 125 psi. The pressure relief valve shall provide overpressure protection for the suction hose even when the intake valve is closed.

A 1/4" air bleeder valve shall be provided and controlled at the pump operator's position.

Intake Relief Valve

The pump shall be equipped with an Akron style 59 cast brass, variable-pressure-setting relief valve on the pump suction side. It shall be designed to operate at a maximum inlet pressure of 250 PSI. The relief valve shall be normally closed and shall be set to begin opening at 125 PSI in order to limit intake pressures in the pumping system. When the relief valve opens, the overflow water shall be directed through a plumbed outlet to discharge below the body in an area visible to the pump operator. The overflow outlet shall terminate with a male 2-1/2" NST threaded fitting to allow the overflow water to be directed away from the vehicle with a short hose (supplied by the fire department) during freezing weather or under other conditions where an accumulation of water around the apparatus might be hazardous.

Front Intake Swivel

A heavy duty 6" 90 degree cast brass elbow designed and constructed specifically for fire/emergency vehicle usage shall serve as the auxiliary front suction inlet. The elbow, also referred to as the "swivel", shall be attached to the front suction piping. This component shall have the following features:

- 1) The ability to rotate 180 degrees.
- 2) A rugged twist-lock mechanism to hold the elbow in place at the desired position.
- 3) A double-ball race with bronze balls.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

- 4) A 5" NPT free swivel female inlet.
- 5) A 6" NST male outlet with strainer.
- 6) Cast brass with polished chrome finish.

The elbow/swivel shall be mounted so that it extends above the extended front bumper.

Front Jumpline

One (1) 1-1/2" preconnect outlet with a manually operated Akron valve shall be supplied to the extended front bumper. The preconnect shall consist of a 2" heavy duty hose coming from the pump discharge manifold to a 2" FNPT x 1-1/2" MNST mechanical swivel hose connection to permit the use of the hose from either side of the apparatus.

The valve shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position with water flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

An air blow-out valve shall be installed between the chassis air reservoir and the front jump line. The control shall be installed on the pump operator's panel.

The discharge shall be supplied with a Class 1 automatic 3/4" drain valve assembly. The automatic drain shall have an all-brass body with stainless steel check assembly. The drain shall normally be open and automatically close when the pressure is greater than 6 psi.

The valve control shall be located at the pump operator panel and shall visually indicate the position of the valve at all times.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance and decreased friction loss.

There shall be a polished stainless steel swivel elbow provided for the front bumper discharge located on top of the bumper officer's side of center tray.

2.5" Single Crosslay

One (1) single crosslay discharge shall be provided at the front area of the body. The crosslay shall have one (1) 2-1/2" mechanical swivel hose connection to permit the use of the hose from either side of the apparatus.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The crosslay hosebed shall consist of a 2-1/2" heavy-duty hose coming from the pump discharge manifold to the 2-1/2" swivel. The hose shall be connected to a manually operated 2-1/2" Akron valve. The valve shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position with water flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

The valve control shall be located at the pump operator's panel and shall visually indicate the position of the valve at all times.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance and decreased friction loss.

2.5" Left Panel Discharges (2)

Two (2) 2-1/2" discharge outlets with a manually operated Akron valves shall be provided at the left hand side pump panel.

The valve shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position and water is flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

The valve control shall be located at the pump operator panel and shall visually indicate the position of the valve at all times.

The discharge shall extend out beyond the pump panel with a 30 degree downward angle with 2-1/2" NST threads to help prevent kinking of the discharge hose. The 30 degree chrome droop shall be an integral part of the discharge valve and shall be equipped with a chrome plated rocker lug cap with a retainer chain.

The discharge shall be supplied with a 3/4" bleeder valve assembly. The bleeder valve shall be installed to drain water from the gauge pressure line to prevent freezing of the line. The drain shall be controlled with a quarter-turn valve on the pump panel.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance and decreased friction loss.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

2.5" Right Intake

One (1) 2-1/2" suction inlet with a manually operated 2-1/2" Akron valve shall be provided on the left side pump panel.

The valves shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position and water is flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

The outlet of the valve shall be connected to the suction side of the pump with the valve body located behind the pump panel. The valve shall come equipped with a brass inlet strainer, 2-1/2" NST female chrome inlet swivel, and shall be equipped with a chrome plated rockerlug plug with a retainer device.

2.5" Right Panel Discharge

One (1) 2-1/2" discharge outlet with a manually operated Akron valve shall be provided at the right side pump panel.

The valve shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position with water flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

The valve control shall be located at the pump operator panel and shall visually indicate the position of the valve at all times.

The discharge shall extend out beyond the pump panel with a 30 degree downward angle with chrome plated 2-1/2" NST threads to help prevent kinking of the discharge hose. The 30 degree chrome droop shall be an integral part of the discharge valve and shall be equipped with a chrome plated rocker lug cap with a retainer chain.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance and decreased friction loss.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

2.5" Left Rear Discharge

One (1) 2-1/2" discharge outlet with a manually operated Akron valve shall be supplied to the left rear of the apparatus by a 2-1/2" stainless steel pipe.

The valve shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position with water flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

The valve control shall be located at the pump operator panel and shall visually indicate the position of the valve at all times.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance and decreased friction loss.

2nd Left Rear 2.5" Discharge

One (1) 2-1/2" discharge outlet with a manually operated Akron valve shall be supplied to the left rear of the apparatus by a 2-1/2" stainless steel pipe.

The valve shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position with water flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

The valve control shall be located at the pump operator panel and shall visually indicate the position of the valve at all times.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance and decreased friction loss.

Location: Inboard of 1st left rear discharge.

2.5" Right Rear Discharge

One (1) 2-1/2" discharge outlet with a manually operated Akron valve shall be supplied to the right rear of the apparatus by a 2-1/2" stainless steel pipe.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The valve shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position with water flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

The valve control shall be located at the pump operator panel and shall visually indicate the position of the valve at all times.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance and decreased friction loss.

Location: (location to be specified).

Deck Gun Discharge

One (1) 3” deck gun discharge outlet with a manually operated Akron valve and 3” stainless steel pipe shall be provided above the pump compartment.

The valve shall be an Akron 8800HD series with a 316 stainless steel ball and dual polymer seats for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the stainless steel ball when in a throttle position with water flowing through it.

The valve shall be of the unique Akron swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

The valve shall be equipped with a device that limits the opening and closing speeds to comply with the current edition of NFPA 1901.

The valve control shall be located at the pump operator`s panel and shall visually indicate the position of the valve at all times.

All fabricated piping shall be a minimum of Schedule 10 stainless steel for superior corrosion resistance and decreased friction loss.

Deck Gun Location

Deck gun piping shall be positioned centered in deck gun channel. This location shall allow for optimal operation of a deck gun monitor once installed.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Extend-A-Gun

A Task Force Tips 18" Extend-A-Gun piping shall be supplied for the deck gun discharge to allow for raising and lowering the deck gun monitor.

The Extend-A-Gun shall include a raised monitor sensor connected to the door ajar light.

4" Right Panel Discharge

One (1) 4" discharge outlet with a 4" electrically-operated Akron valve shall be provided at the side pump panel. The discharge shall consist of a 4" valve connected to a 4" MNST adapter. The adapter shall protrude through the pump panel. The end of the discharge adapter shall be equipped with a chrome-plated, rocker-lug cap with a retainer chain.

The valve shall be an Akron 8600HD series with 316 stainless ball and polymer seals for ease of operation and increased abrasion resistance. The valve shall have a self-locking ball feature using an automatic friction lock design to balance the chrome-plated brass ball when in a throttle position with water flowing through it. The valve shall be of the unique Akron Swing-out design to allow the valve body to be removed for servicing without disassembling the plumbing.

The valve shall utilize an electric driven worm gear actuator with a Navigator 9323 controller. The 9323 controller shall be located at the pump operator's panel and contain indicator lights for open, closed and throttled valve positions. The valve may also be operated manually in case of electrical system failure.

IC Push/Pull Controls

The apparatus pump panel shall be equipped with Innovative Controls Side Mount Valve Controls. The ergonomically designed ¼ turn push-pull T-handle shall be chrome-plated zinc with recessed labels for color-coding and verbiage. An anodized aluminum control rod and housing shall, together with a stainless spring steel locking mechanism, eliminate valve drift. Teflon impregnated bronze bushings in both ends of the rod housing shall minimize rod deflection, never need lubrication, and ensure consistent long-term operation. The control assembly shall include a decorative chrome-plated zinc panel-mounting bezel with areas for color-coding and/or FOAM and CAFS identification labels.

Bleeder Drain Valves

The bleeder/drain valves shall be Innovative Controls ¾" ball brass drain valves with a chrome-plated 1/4 turn handle. Each 1/4 turn handle grip shall feature built-in color-coding labels and a verbiage tag identifying each valve.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Discharge/Intake Bezel

Innovative Controls intake and/or discharge swing handle bezels shall be installed to the apparatus with mounting bolts. These bezel assemblies will be used to identify intake and/or discharge ports with color and verbiage. These bezel are designed and manufactured to withstand the specified apparatus service environment and shall be backed by a warranty equal to that of the exterior paint and finish. The specified assemblies feature a chrome-plated panel-mount bezel with durable UV resistant polycarbonate inserts. These UV resistant polycarbonate graphic inserts shall be sub-surface screen printed to eliminate the possibility of wear and protect the inks from fading. All insert labels shall be backed with 3M permanent adhesive (200MP), which meets UL969 and NFPA standards.

FRC PumpBoss Pressure Governor

Fire Research PumpBoss model PBA400 pressure governor and monitoring display kit shall be installed. The standard kit shall include a control module, pump discharge pressure sensor, and cables. The control module case shall be waterproof and have dimensions not to exceed 6-3/4" high by 4-5/8" wide by 1-3/4" deep. Inputs for engine information shall be from a J1939 databus or from independent sensors and pump discharge pressure input shall be from a pressure sensor.

The following continuous displays shall be provided:

- * CHECK ENGINE and STOP ENGINE warning LEDs.
- * Engine RPM; shown with four daylight bright LED digits more than 1/2" high.
- * Engine OIL PRESSURE; shown on an LED bar graph display in 10 psi increments.
- * Engine TEMPERATURE; shown on an LED bar graph display in 10 degree increments.
- * BATTERY VOLTAGE; shown on an LED bar graph display in 0.5 volt increments.
- * PSI / RPM setting; shown on a dot matrix message display.
- * PSI and RPM mode LEDs.
- * THROTTLE READY LED.

A dot-matrix message display shall show diagnostic and warning messages as they occur. It shall show monitored apparatus information, stored data, and program options when selected by the operator.

The program shall store the accumulated operating hours for the pump and engine, previous incident hours, and current incident hours in a non-volatile memory. Stored elapsed hours shall be displayed at the push of a button. It shall monitor inputs and support audible and visual warning alarms for the following conditions:

- * Low Oil Pressure
- * High Engine Coolant Temperature
- * High Transmission Temperature
- * Low Battery Voltage (Engine Off)
- * Low Battery Voltage (Engine Running)

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

- * High Battery Voltage
- * High Engine RPM

The governor shall operate in two control modes; pressure and RPM. No discharge pressure or engine RPM variation shall occur when switching between modes. A control knob that uses optical technology shall adjust pressure or RPM settings. It shall be 2" in diameter with no mechanical stops, a serrated grip, and have a red idle push button in the center.

A throttle ready LED shall light when the pump engaged interlock signal is recognized. The governor shall be in pressure mode and set the engine RPM to idle. In pressure mode the governor shall automatically regulate the discharge pressure at the level set by the operator. In RPM mode the governor shall maintain the engine RPM at the level set by the operator except in the event of a discharge pressure increase. The governor shall limit a discharge pressure increase in RPM mode to a maximum of 30 PSI. Other safety features shall include recognition of no water conditions with an automatic programmed response and a push button to return the engine to idle.

The pressure governor and monitoring display shall be programmed to interface with a specific engine.

The display module shall be mounted at the pump operator's panel.

Master Gauges (2)

A Class 1 weatherproof 6" compound vacuum pressure gauge with a range of 30-0-400 shall be installed on the pump panel. The gauge shall be filled with a liquid solution.

2.5" Discharge Gauges (10)

The valve discharge gauges shall be 2 1/2"(63mm) diameter Innovative Controls pressure gauges. Each gauge shall have a rugged corrosion free stainless steel case and clear scratch resistant molded crystals with captive O-ring seals to ensure distortion free viewing and seal the gauge. The gauges shall be filled with a synthetic mixture to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40F to +160F. Each gauge shall exceed ANSI B40.1 Grade A requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated stainless steel bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauges shall be installed into decorative chrome-plated mounting bezels that incorporate valve-identifying verbiage and/or color labels. The gauges shall display a range from 0 to 400 psi with black graphics on a white background.

FRC Water Tank Level Gauge

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

Fire Research TankVision Pro model WLA300-A00 tank indicator kit shall be installed. The kit shall include an electronic indicator module, a pressure sensor, and a 10' sensor cable. The indicator shall show the volume of water in the tank on nine (9) easy to see super bright RGB LEDs. A wide view lens over the LEDs shall provide for a viewing angle of 180 degrees. The indicator case shall be waterproof, manufactured of Polycarbonate/Nylon material, and have a distinctive blue label.

The program features shall be accessed from the front of the indicator module. The program shall support self-diagnostics capabilities, self-calibration, six (6) programmable colored light patterns to display tank volume, adjustable brightness control levels and a datalink to connect remote indicators. Low water warnings shall include flashing LEDs at 1/4 tank, down chasing LEDs when the tank is almost empty, and an output for an audio alarm.

The indicator shall receive an input signal from an electronic pressure sensor. The sensor shall be mounted from the outside of the water tank near the bottom. No probe shall be placed on the interior of the tank. Wiring shall be weather resistant and have automotive type plug-in connectors.

Multiplex Electrical System

Electrical System

The apparatus shall incorporate a Weldon V-MUX multiplex 12 volt electrical system. The system shall have the capability of delivering multiple signals via a CAN bus. The electrical system installed by the apparatus manufacturer shall conform to current SAE standards, the latest FMVSS standards, and the requirements of the applicable NFPA 1901 standards.

The electrical system shall be pre-wired for optional computer modem accessibility to allow service personnel to easily plug in a modem to allow remote diagnostics.

The electrical circuits shall be provided with low voltage over-current protective devices. Such devices shall be accessible and located in required terminal connection locations or weather-resistant enclosures. The over-current protection shall be suitable for electrical equipment and shall be automatic reset type and meet SAE standards. All electrical equipment, switches, relays, terminals, and connectors shall have a direct current rating of 125 percent of maximum current for which the circuit is protected. The system shall have electro-magnetic interference suppression provided as required in applicable SAE standards.

Any electrical junction or terminal boxes shall be weather-resistant and located away from water spray conditions.

Multiplex System

For superior system integrity, the networked multiplex system shall meet the following minimum component requirements:

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

- The network system must be Peer to Peer technology based on RS485 protocol. No one module shall hold the programming for other modules. One or two modules on a network referred to as Peer to Peer, while the rest of the network consists of a one master and several slaves is not considered Peer to Peer for this application.
- Modules shall be IP67 rated to handle the extreme operating environment found in the fire service industry.
- All modules shall be solid state circuitry utilizing MOS-FET technology and utilize Deutsch series input/output connectors.
- Each module that controls a device shall hold its own configuration program.
- Each module should be able to function as a standalone module. No “add-on” module will be acceptable to achieve this form of operation.
- Load shedding power management (8 levels).
- Switch input capability for chassis functions.
- Responsible for lighting device activation.
- Self-contained diagnostic indicators.
- Wire harness needed to interface electrical devices with multiplex modules.
- The grounds from each device should return to main ground trunk in each sub harness by the use of ultrasonic splices.

Wiring

All harnessing, wiring and connectors shall be manufactured to the following standards/guidelines. No exceptions.

- NFPA 1901-Standard for Automotive Fire Apparatus
- SAE J1127 and J1127
- IPC/WHMA-A-620 – Requirements and Acceptance for Cable and Wire Harness Assemblies. (Class 3 – High Performance Electronic Products)

All wiring shall be copper or copper alloys of a gauge rated to carry 125 of the maximum current for which the circuit is protected. Insulated wire and cable 8 gauge and smaller shall be SXL, GXL, or TXL per SAE J1128. Conductors 6 gauge and larger shall be SXL or SGT per SAE J1127.

All wiring shall be colored coded and imprinted with the circuits function. Minimum height of imprinted characters shall not be less than .082” plus or minus .01”. The imprinted characters shall repeat at a distance not greater than 3”.

A coil of wire shall be provided behind electrical appliances to allow them to be pulled away from mounting area for inspection and service work.

Wiring Protection

The overall covering of the conductors shall be loom or braid.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Braid style wiring covers shall be constructed using a woven PVC-coated nylon multifilament braiding yarn. The yarn shall have a diameter of no less than .04" and a tensile strength of 22 lbs. The yarn shall have a service temperature rating of -65 F to 194 F. The braid shall consist of 24 strands of yarn with 21 black and 3 yellow. The yellow shall be oriented the same and be next to each other.

Wiring loom shall be flame retardant black nylon. The loom shall have a service temperature of -40 F to 300 F and be secured to the wire bundle with adhesive-backed vinyl tape.

Wiring Connectors

All connectors shall be Deutsch series unless a different series of connector is needed to mate to a supplier's component. The connectors and terminals shall be assembled per the connector/terminal manufacturer's specification. Crimble/Solderless terminals shall be acceptable. Heat shrink style shall be utilized unless used within the confines of the cab.

NFPA Required Testing of Electrical System

The apparatus shall be electrical tested upon completion of the vehicle and prior to delivery. The electrical testing, certifications, and test results shall be submitted with delivery documentation per requirements of NFPA 1901. The following minimum testing shall be completed by the apparatus manufacturer:

1. Reserve capacity test:

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes. All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test fail.

2. Alternator performance test at idle:

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

3. Alternator performance test at full load:

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system shall be permitted during this test. However, an alarm sounded by excessive battery discharge, as detected by the system required in NFPA 1901

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Standard, or a system voltage of less than 11.7 volts DC for a 12 volt nominal system, for more than 120 seconds, shall be considered a test failure.

4. Low voltage alarm test:

Following the completion of the above tests, the engine shall be shut off. The total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals. With the load still applied, a reading of less than 11.7 volts DC for a 12 volt nominal system shall be considered a test failure. The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

NFPA Required Documentation

The following documentation shall be provided on delivery of the apparatus:

- A. Documentation of the electrical system performance tests required above.
- B. A written load analysis, including:
 - a. The nameplate rating of the alternator.
 - b. The alternator rating under the conditions.
 - c. Each specified component load.
 - d. Individual intermittent loads.

Vehicle Data Recorder

A vehicle data recorder system shall be provided to comply with the 2009 and 2016 editions of NFPA 1901. The following data shall be monitored:

- Vehicle speed MPH
- Acceleration (from speedometer) MPH/Sec.
- Deceleration (from speedometer) MPH/Sec.
- Engine speed RPM
- Engine throttle position % of full throttle
- ABS Event On/Off
- Seat occupied status Occupied Yes/No by position
- Seat belt status Buckled Yes/No by position
- Master Optical Warning Device Switch On/Off
- Time: 24 hour time
- Date: Year/Month/Day

Occupant Detection System

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

There shall be a visual and audible warning system installed in the cab that indicates the occupant buckle status of all cab seating positions that are designed to be occupied during vehicle movement.

The audible warning shall activate when the vehicle's park brake is released and a seat position is not in a valid state. A valid state is defined as a seat that is unoccupied and the seat belt is unbuckled, or one that has the seat belt buckled after the seat has been occupied.

The visual warning shall consist of a graphical representation of each cab seat in the multiplex display screen that will continuously indicate the validity of each seat position.

The system shall include a seat sensor and safety belt latch switch for each cab seating position, audible alarm and braided wiring harness.

Multiplex Display

The V-MUX multiplex electrical system shall include a Vista IV color display.

The display shall have the following features:

- Aspect ratio of 16:9 (Wide Screen)
- Diagonal measurement of no less than 7"
- Master warning switch
- Engine high idle switch
- Five (5) tactile switches to access secondary menus
- Eight (8) multi-function programmable tactile switches
- Specific door ajar indication
- Real time clock
- Provides access to the multiplex system diagnostics
- Video capability for optional back-up camera(s) and GPS display

The display shall be located driver's side engine cover.

Electrical Connection Protection

The vehicle electrical system shall be made more robust by the application of a corrosion inhibiting spray coating on all exposed electrical connections on the chassis and body. If equipped with an aerial device, the exposed connections on the aerial components shall also be protected.

The coating shall use nanotechnology to penetrate at the molecular level into uneven surfaces to create a protective water repellant film. The coating shall protect electrical connections against the environmental conditions apparatus are commonly exposed to.

Light Bar Mounts

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

One (1) pair of Whelen 5" tall (model MK8H) aluminum high mounts shall be provided on the front light bar.

Front Light Bar Color(s)

The front light bar shall be provided with the following color LED modules: Red/White with clear lenses

If applicable, includes side facing light bars when colors are the same.

Light Bar

A Whelen Freedom IV Series 72" LED light bar model F4X7 with fourteen (14) LED modules shall be provided; two (2) front corner mounted LED modules, ten (10) forward facing LED modules and two (2) side facing LED modules (with front vista windows) or two (2) rear corner LED modules (without front vista windows).

No rear facing LEDs.

The light bars shall have clear lenses.

The white LEDs (if equipped) shall be switched off in blocking right of way mode.

The light bar shall be installed centered on the front cab roof.

Light Bars

A pair of side facing Whelen Mini Freedom IV Series 21.5" LED light bars shall be provided. Each light bar shall contain four (4) LED modules. Each side facing light bar shall contain one (1) corner LED module forward facing, two (2) side facing LED modules and one (1) corner LED module rearward facing.

The white LEDs (if equipped) shall be switched off in blocking right of way mode.

The light bars shall be installed in the following location: each side over front cab doors.

Light Bar Mounts

One (1) pair of Whelen 5" tall (model MK8H) aluminum high mounts shall be provided on the side facing mini light bars.

Lower Level Warning Light Package

Eight (8) Whelen M6R Super LED red light heads and two (2) Whelen M2R Super LED red light heads shall be provided.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The lights shall include chrome flanges where applicable. The lights shall be wired with weatherproof connectors and shall be mounted as close to the corner points of the apparatus as is practical as follows:

- Two (2) Whelen M6R Super LED Red lights on the front of the apparatus facing forward
- Two (2) Whelen M6R Super LED Red lights on the rear of the apparatus facing rearward
- Two (2) lights each side of the apparatus, one (1) Whelen M6R Super LED Red each side at the forward most point (as practical), and one (1) Whelen M2R Super LED Red each side at the rearward most point (as practical).
- One (1) Whelen M6R Super LED Red light each side of the apparatus centrally located to provide mid ship warning light.

The side facing lights shall be located at forward most position, centered in rear wheelwell, and side facing at rear of body in rubrail if equipped.

All warning devices shall be surface mounted in compliance with NFPA standards.

Upper Rear Warning Lights

Two (2) Whelen model B6MMRRP beacons with Red domes shall be supplied.

The lights shall be located rear upper body on aerial style brackets to meet upper Zone C requirements.

Hazard (Door Ajar) Light

There shall be a Whelen Model M2WR red LED hazard light with black bezel installed as specified.

The light shall be located center overhead.

Warning Lights

Two (2) Whelen ION-T Series model TLI Super LED light heads shall be provided. The lights shall be Red with clear lenses. The lights shall include chrome flanges where applicable.

Location: (1) each side in pump module rubrail if equipped.

Electronic Siren

A Federal PA300 siren model 690010 solid state electronic siren with attached noise-canceling microphone shall be installed. The unit shall be capable of driving a single high power speaker up to 200 watts to achieve a sound output level that meets Class "A" requirements.

Operating modes shall include Hi-Lo, yelp, wail, P.A., air horn and radio re-broadcast.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The siren shall be recessed mounted in the cab.

Electronic Siren Control Location

The electronic siren control shall be located in the center overhead console offset to driver side.

Mechanical Siren

A chrome plated flush mounted Federal Q2B-NN coaster siren shall be installed in the front bumper. An electric siren brake switch shall be located in the cab accessible to driver.

The siren shall be located driver side front bumper.

Siren Speaker

One (1) Federal Signal model ES100 Dynamax 100 watt speaker shall be flush mounted as far forward and as low as possible on the front of the vehicle. A polished model MSFMT with grille shall be provided on the outside of the speaker to prevent road debris from entering the speaker.

Speaker dimensions shall be: 5.5 in. high x 5.9 in. wide x 2.5 in. deep. Weight = 5.5 lbs.

The speaker shall produce a minimum sound output of 120 dB at 10 feet to meet current NFPA 1901 requirements.

The speaker shall be located officer side front bumper inboard of frame.

License Plate Light

One (1) Truck-Lite model 15905 white LED license plate light mounted in a Truck-Lite model 15732 chrome plated plastic license plate housing shall be mounted at the rear of the body.

LED Marker Lights

LED clearance/marker lights shall be installed as specified.

Upper Cab:

- Five (5) amber LED clearance lights on the cab roof.

Lower Cab:

- One (1) amber LED side turn/marker each side of cab ahead of the front door hinge.

Upper Body:

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

- One (1) red Trucklite LED clearance light each side, rear of body to the side.

Lower Body:

- Three (3) red Trucklite LED clearance lights centered at rear, recessed in the rub rail.
- One (1) red Trucklite LED clearance light each side at the trailing edge of the apparatus body, recessed in the rub rail.
- One (1) amber Trucklite LED clearance/auxiliary turn light each side front of body/module, recessed in the rub rail.

Marker Lights

One (1) pair of Britax model L427.203L.12V LED amber/red marker rubber housed lights shall be provided. The lights shall be located on the rear body corners mounted in the down angle position. The red lenses shall illuminate to the rear of the apparatus and the amber shall illuminate to the front of the apparatus. The lights shall be wired to the marker light circuit.

Tail Lights

Three (3) Whelen model M6 series LED (Light Emitting Diode) lights shall be installed in a four (4) light vertical housing each side at rear and wired with weatherproof connectors.

Light functions shall be as follows:

- LED red running light with red brake light in upper position.
- LED amber populated arrow pattern turn signal in middle position.
- LED clear back-up light in lower position.

A one-piece chrome plastic housing shall be mounted around the three (3) individual lights in a vertical position. The lower space will be used by the M6 or equivalent lower NFPA warning light.

Turn Signals

A pair of Weldon model 9186-8580-29 bubble style LED amber auxiliary turn signals with stainless steel bezels shall be installed.

Location: (1) each side of cab centered over wheelwell.

Medical Cabinet Lighting [Qty: 3]

One (1) ROM V4 LED compartment light strip shall be mounted in the medical cabinet(s).

The light bar shall include super bright white LEDs mounted to circuit boards that have acrylic conformal coating for corrosion protection. The LED circuit boards shall be mounted to an

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

extruded aluminum base with lexan lens. The light shall produce 250 lumens per foot and be waterproof up to 1 meter (3.3 feet).

The light shall be controlled by a compartment door switch.

Compartment Light Package

One (1) ROM V4 compartment light strip shall be mounted in each body compartment greater than 4 cu. ft. Transverse compartments shall have two (2) lights, located one (1) each side.

Each light bar shall include super bright white LEDs mounted to circuit boards that have acrylic conformal coating for corrosion protection. The LED circuit boards shall be mounted to an extruded aluminum base with lexan lens. The light shall produce 250 lumens per foot and be waterproof up to 1 meter (3.3 feet).

Compartment lights shall be wired to a master on/off rocker switch on the cab switch panel.

The wiring connection for the compartment lights shall be made with a weather-resistant plug in style connector. A single water and corrosion-resistant switch with a polycarbonate actuator and sealed contacts shall control each compartment light. The switch shall allow the light to illuminate if the compartment door is open.

Ground Lights

The apparatus shall be equipped with a sufficient quantity of lights to properly illuminate the ground areas around the apparatus in accordance with current NFPA requirements. The lights shall be 4" circular LED (Light Emitting Diode) with clear lenses mounted in a resilient shock absorbent mount for improved bulb life. The wiring connections shall be made with a weather resistant plug in style connector.

Ground area lights shall be switched from the cab dash with the work light switch.

One (1) ground light shall be supplied under each side of the front bumper extension if equipped.

Lights in areas under the driver and crew area exits shall be activated automatically when the exit doors are opened.

Additional Ground Lights

An additional recessed 4" LED light with clear lens shall be provided to illuminate the ground at the location specified.

Location – below L1, L3, R1, R3.

Hosebed Light Wired to Back-Up Lights

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

The hosebed light shall be activated when the chassis is placed in reverse to provide additional lighting, in addition to the back-up lights, when backing the vehicle.

Deck/Scene Light Wired to Back-Up Lights

The rear deck or scene lights shall be activated when the chassis is placed in reverse to provide additional lighting, in addition to the back-up lights, when backing the vehicle.

Cab Scene Light Switching

The cab scene lights shall be wired to activate through the appropriate side cab door ajar switch. This application allows the cab scene lights to be used as additional illumination of the ground area for personnel entering or exiting the vehicle. The switching for this application is in addition to the standard cab scene light switching.

Scene Lights

Two (2) Whelen model M6ZC series Linear Super LED clear scene lights shall be provided.

Each shall have Linear Super LED diodes with internal light deflecting optics. The internal light deflecting optics shall redirect the light without the use of angle brackets.

The lights shall be located (1) each side rear compartment face up high, (1) each side of cab, rearward of forward doors, up high and be controlled by a switch in cab accessible to driver (lights on sides of apparatus to be switched separately).

Crosslay Light

A Whelen LED light model PFBP12C shall be installed at the rear area of the crosslay to provide crosslay lighting per current NFPA 1901. The crosslay light shall be switched with work light switch in the cab.

Hosebed Light

One (1) Amdor H2O Luma-Bar shall be installed at the front area of the hosebed to provide hosebed lighting per current NFPA 1901. All electrical connectors are to be enclosed in the housing providing protection against the elements.

The hosebed light shall be switched with work light switch in the cab.

Engine Compartment Light

There shall be lighting provided in compliance with NFPA to illuminate the engine compartment area. The light wiring circuit shall activate when the cab is tilted and master power is switched on.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Pump Compartment LED Light

An LED light shall be provided in the pump compartment area for NFPA compliance. The light shall be wired to operate with the work light switch in the cab.

Map Light

A Federal "Littlite" LED map light model LF18-LED shall be supplied. The map light shall be 12 volt with 18" flexible gooseneck and a matte black finish. The light shall have a switch provided for white or red illumination. It shall be located at officer's A post.

Pump Panel Light Package

Six (6) LED pump panel lights shall be provided. The lights shall be located three (3) each side under a light shield (as applicable with intermediate steps) directly above the left and right side pump panels. The lights shall be Tecniq EON with polished stainless steel housings. The light shields shall be formed from 14 gauge brushed finish stainless steel. The work light switch in the cab shall activate the lights when the park brake is set.

LED Backing Lights

A pair of TecNiq model E61-WS00-1 LED surface mount docking/backing lights shall be provided. Each light shall provide additional lighting for backing the vehicle and shall operate when the vehicle is placed in reverse.

The lights shall be located rear wheelwell offset to rear.

Specifications:

Dimensions: 5.76"x 1"x 3.27"

LEDs: 3

Lumens: 1400

Voltage: 9 - 30 VDC

Current: 0.85A - 1.15A

Wire: 12"

Mounting: Surface mounted with two screws

LED Colors: White

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Door Ajar Alarm

An audible alarm shall be provided through the V-Mux display in the cab wired into the door ajar or indicator.

Foot Switch

A heavy duty metal floor mounted foot switch shall be installed to operate the Q2B siren. It shall be located driver's side.

Additional Switches (2)

A 12 volt switch shall be provided.

The switch shall be located driver rear of body for rear work lights, officer's side switch panel for Q2B brake.

110 Volt Switches

A relay shall be provided to allow operation of the specified 110/240 volt device from a remote location other than the circuit breaker box. The relay shall be mounted in a weather resistant enclosure mounted near the breaker box or as instructed from engineering. A remote switch shall be mounted as specified.

Location: programmed to multiplex display for cab brow 120/240V scene light(s).

Camera Shield

A diamond plate protective shield shall be provided for the top and sides of a camera. The shield shall be designed not to impede in the operational envelope of the camera.

Camera Back-Up

There shall be a Voyager camera model number VCCS150B provided mounted on the rear of the apparatus. The camera shall feature a wide angle lens, IR LED assisted illumination for enhanced low-light performance, non-corrosive mounting bracket, and stainless steel hardware. The camera shall be interlocked with the chassis transmission. When the apparatus is placed in reverse the camera shall automatically be activated and when the transmission is placed in any other gear the screen shall return to the previously displayed screen.

The camera shall having the following specifications:

- NTSC/PAL Video output signal format
- 150° Viewing angle
- Housing: Aluminum

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

- Waterproof: IPX7
- Built-in microphone
- Dimensions: 2.7" W x 1.7" H x 2.5" D

The camera shall be located at the rear of the truck, up as high as possible. Optimize mounting position using space not allocated by other equipment/options unless otherwise specified.

Back-Up Alarm

An electronic back-up alarm shall be supplied. The 97 dB alarm shall be wired into the chassis back-up lights to signal when the vehicle is in reverse gear.

12 Volt DC Power Distribution Module

There shall be a 12 place 12 volt DC power distribution module installed as specified.

The module will have six (6) circuits wired directly to the battery and have six (6) circuits wired through the master battery switch with 12 positions for grounds. Connection to the power module circuit will be through a .250 female spade connector. Each buss will be protected with a 50 amp circuit breaker for overload protection. The module will accept ATC blade type fuses or 22X series circuit breakers.

The module shall be located behind officer's seat.

12 Volt Power Leads

One (1) 12 volt 12 gauge constant hot lead shall be provided. The lead shall be 24" long and include a ground wire and fuse.

The lead shall be located L3 upper forward wall, R3 upper forward wall.

Hydraulic Generator

A Smart Power model HR-110 top mount style 10000 watt hydraulic generator shall be provided. The generator shall be installed dunnage pan offset to driver side.

The unit shall come equipped with: modular generator unit (which includes the hydraulic motor and filter, generator, and cooler), axial piston hydraulic pump, hydraulic reservoir, and a gauge panel.

The gauge panel shall display voltage, hour meter, frequency, and amperage.

The hydraulic motor, generator, blower, cooler, and necessary hydraulic components shall be mounted in a rugged steel case.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The modular generator unit shall be 32” long x 13.50” wide x 17.00” high and weigh approximately 240 pounds.

The hydraulic pump shall be driven by a chassis transmission mounted power take off (PTO).

A generator control / PTO engage switch shall be mounted on the cab instrument panel to engage the PTO and start the generator.

Ratings and Capacity

Rating:	10000 watts continuous 12000 watts peak
Volts:	120/240 volts
Phase:	Single, 4 wire
Frequency:	60 Hz
Amperage:	83 amps @ 120 volts or 42 amps @ 240 volts
Engine speed at engagement:	Recommend below 1000 RPM
Operation range:	800 to 2100 RPM

Testing

The generator shall be tested in accordance with current NFPA 1901 standards.

Notes:

- *All ratings and capacities shall be derived utilizing current NFPA 1901 test parameters.
- *Extreme ambient temperatures could affect generator performance.

3rd Party Generator Testing

The generator shall be tested at the manufacturer`s facility by an independent, third-party testing service. The conditions and testing of the generator shall be as outlined in current NFPA 1901.

The test shall include operating the generator for two hours at 100% of the rated load. Power source voltage, amps, frequency shall be monitored. The prime mover`s oil pressure, water temperature, transmission temperature (if applicable) and power source hydraulic fluid temperature (if applicable) shall be monitored during testing.

The results of the test shall be recorded and provided with delivery documentation.

Circuit Breaker Panel

A twelve (12) place breaker box with up to twelve (12) appropriately sized ground-fault interrupter circuit breakers shall be supplied. The breaker box will include a master breaker sized according to the generator output. The breaker box will be located in the specified compartment, not to exceed 12` run of wire. Dimensions - 17.92” high x 14.25” wide x 3.75” deep.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

Location: L1 back wall above offset forward area.

Whelen Pioneer 120V LED Flood Lights (2)

A Whelen Pioneer Plus series 120V flood light model PFP2AC dual panel LED light head shall be provided on a cab brow mount. The rectangular extruded light fixture with die cast end caps shall measure 14" wide by 4-5/8" high by 3" deep and have a white powder coat finish. The light fixture shall have a dual panel (4) clusters of LED lamps with molded vacuum metalized reflector that draws 1.25 amps and produce 11,000 usable lumens.

The light shall be located driver and officer side front cab brow.

LED Light Tower

A Command Light model KL415A light tower shall be provided. The light tower shall be a two-stage articulating device with a lighting bank on top of a second stage capable of 360 degrees continuous rotation. The light shall be elevated by electric linear actuators, one (1) actuator shall elevate the light bank, and one (1) actuator shall adjust the light bank angle from 0 to 110 degrees. The overall extended height from the base to the top pair of lights shall be 87.5".

The light bank shall have six (6) Whelen Pioneer PFP2 150 watt output 120V, LED lights. Light heads shall be mounted in three (3) pairs, giving three (3) vertical lines of two (2) when the lights are in the upright position. Power for light bank shall be transmitted through power collecting rings thus allowing 360+ degrees rotation in either direction, NO EXCEPTIONS.

Light tower shall be controlled with a hand-held umbilical line remote control. The storage station for the remote control unit shall be equipped with a button to activate the "Auto-Park" automatic nesting feature. The controls on the remote box shall be:

1. Three (3) switches, one (1) for each light bank.
2. One (1) light bank rotation switch.
3. One (1) switch for elevating lower stage.
4. One (1) switch for elevating upper stage.
5. One (1) indicator light to indicate when light bank is out of roof nest position.
6. One (1) indicator light to indicate when light bank is rotated to proper nest position.
7. One (1) on/off switch for the top mounted strobe.

The controls shall be located next to the circuit breaker box.

The tower base shall have a light that illuminates the envelope of motion during any movements of the light tower mast.

The Command Light assembly shall be all aluminum construction, with stainless steel shafts and bronze bushings for long life and low maintenance.

KINGSTON FIRE DISTRICT

SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The overall size of nested light tower shall be approximately 33" wide x 47" long x 13" high and weigh approximately 310 lbs.

The light tower shall be located ahead of vista mounted side to side and hinged to driver side.

Cab Receptacles (3)

20 amp/110 volt 3-prong straight blade NEMA 5-20 duplex household receptacle with stainless steel cover plate shall be installed in a non-weather exposed area as specified by the department. The receptacle shall be wired to the inlet receptacle where it will have overcurrent protection from an external source.

Location - in cab officer side on 3 x 3 post rear facing just above engine cover, center back wall of cab, officer back wall of cab.

DOT Required Drive Away Kit

Three (3) triangular warning reflectors with carrying case shall be supplied to satisfy the DOT requirement.

Un-Painted Pump/Pre-Connect Module(s)

All applicable pump application modules shall have a sanded finish (not painted job color). Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module shall be painted job color.

Paint Wheels

The chassis wheels (inboard and outboard) shall be painted job color. The paint shall be of the highest quality finish for low maintenance, long life, and attractive appearance. The finish shall consist of a corrosion-resistant primer, urethane high build primer, and high performance durable color coat.

The paint process shall meet or exceed current State regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water and soil. Manufacturer shall, upon demand, provide evidence that the manufacturing facility is in compliance with State EPA rules and regulations.

Paint process shall feature Akzo-Nobel's high solid LV products and be performed in the following steps:

- Corrosion Prevention - all raw material shall be pre-treated with the Weather Jacket Corrosion Prevention system to provide superior corrosion resistance and excellent adhesion of the top coat.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

- Akzo-Nobel Sealer/Primer LV - acrylic urethane sealer/primer shall be applied to guarantee excellent gloss hold-out, chip resistance and a uniform base color.
- Akzo-Nobel High Solid LV (Top coat) - a lead-free, chromate-free high solid acrylic urethane top coat shall be applied, providing excellent coverage and durability. A minimum of two (2) coats shall be applied.
- Akzo-Nobel High Solid LV (Clear coat) - high solid LV clear coat shall be applied as the final step in order to ensure full gloss and color retention and durability. A minimum of two (2) coats shall be applied.

Paint Valve Ends

The valve ends shall be painted job color.

Cab Paint

The apparatus cab shall be painted Sikkens FLNA3225E-1 Red. The paint process shall meet or exceed current state regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water, and soil. Contractor shall, upon demand, provide evidence that the manufacturing facility is in compliance with State EPA rules and regulations.

The aluminum cab exterior shall have no mounted components prior to painting to assure full coverage of metal treatments and paint to the exterior surfaces. Cab doors and any hinged smooth-plate compartment doors shall be painted separately to assure proper paint coverage on cab, door jambs and door edges.

Paint process shall feature Sikkens high solid LV products and be performed in the following steps:

- Corrosion Prevention - all aluminum surfaces shall be pre-treated with the Alodine 5700 conversion coating to provide superior corrosion resistance and excellent adhesion of the base coat.
- Sikkens Sealer/Primer LV - acrylic urethane sealer/primer shall be applied to guarantee excellent gloss hold-out, chip resistance and a uniform base color.
- Sikkens High Solid LVBT650 (Base coat) - a lead-free, chromate-free high solid acrylic urethane base coat shall be applied, providing excellent coverage and durability. A minimum of two (2) coats shall be applied.
- Sikkens High Solid LVBT650 (Clear coat) - high solid LV clear coat shall be applied as the final step in order to ensure full gloss and color retention and durability. A minimum of two (2) coats shall be applied.

Any location where aluminum is penetrated after painting, for the purpose of mounting steps, hand rails, doors, lights, or other specified components shall be treated at the point of penetration with a corrosion inhibiting pre-treatment (ECK Corrosion Control). The pre-treatment shall be applied to the aluminum sheet metal or aluminum extrusions in all locations where the aluminum

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

has been penetrated. All hardware used in mounting steps, hand rails, doors, lights, or other specified components shall be individually treated with the corrosion inhibiting pre-treatment.

After the paint process is complete, the gloss rating of the unit shall be tested with a 20 degree gloss meter. Coating thickness shall be measured with a digital MIL gauge and the orange peel with a digital wave scan device.

Cab Two-Tone Paint

The upper section of the cab shall be painted FLNA4145 Black.

The paint process of the secondary cab color shall be the same as the primary color.

Paint Break with Dip to Grille

The cab shall have a two-tone paint break. The break line shall be approximately 31.5 inches below the cab roof drip rail. The paint break shall include a dip down to the corners of the cab grille.

Body Paint

The apparatus body shall be painted Sikkens FLNA3225E-1 Red. The paint process shall meet or exceed current state regulations concerning paint operations. Pollution control shall include measures to protect the atmosphere, water, and soil. Contractor shall, upon demand, provide evidence that the manufacturing facility is in compliance with State EPA rules and regulations.

The aluminum body exterior shall have no mounted components prior to painting to assure full coverage of metal treatments and paint to the exterior surfaces of the body. Any vertically or horizontally hinged smooth-plate compartment doors shall be painted separately to assure proper paint coverage on body, door jambs and door edges.

Paint process shall feature Sikkens high solid LV products and be performed in the following steps:

- Corrosion Prevention - all aluminum surfaces shall be pre-treated with the Alodine 5700 conversion coating to provide superior corrosion resistance and excellent adhesion of the base coat.
- Sikkens Sealer/Primer LV - acrylic urethane sealer/primer shall be applied to guarantee excellent gloss hold-out, chip resistance and a uniform base color.
- Sikkens High Solid LVBT650 (Base coat) - a lead-free, chromate-free high solid acrylic urethane base coat shall be applied, providing excellent coverage and durability. A minimum of two (2) coats shall be applied.
- Sikkens High Solid LVBT650 (Clear coat) - high solid LV clear coat shall be applied as the final step in order to ensure full gloss and color retention and durability. A minimum of two (2) coats shall be applied.

KINGSTON FIRE DISTRICT **SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER**

Any location where aluminum is penetrated after painting, for the purpose of mounting steps, hand rails, doors, lights, or other specified components shall be treated at the point of penetration with a corrosion inhibiting pre-treatment (ECK Corrosion Control). The pre-treatment shall be applied to the aluminum sheet metal or aluminum extrusions in all locations where the aluminum has been penetrated. All hardware used in mounting steps, hand rails, doors, lights, or other specified components shall be individually treated with the corrosion inhibiting pre-treatment.

After the paint process is complete, the gloss rating of the unit shall be tested with a 20 degree gloss meter. Coating thickness shall be measured with a digital MIL gauge and the orange peel with a digital wave scan device.

Cab Interior Paint

The interior of the cab shall be painted Zolatone gray #20-64. Prior to painting, all exposed interior metal surfaces shall be pretreated using a corrosion prevention system.

Lettering and Striping

A 6" NFPA compliant cab/body scotchlite stripe with 1" stripe above/below, and up to one hundred (100) scotchlite letters with shade/outline shall be applied per Fire Department design.

The reflective stripe in the body rubrail shall be black.

Rear Body Chevron

50% of the rear body shall be covered with reflective striping per Department design.

Designated Standing / Walking Area Indication

1" wide yellow perimeter marking consisting of individual Reflexite diamonds shall be applied to indicate the outside edge of designated standing and walking areas above 48" from the ground in compliance with 2016 NFPA 1901. Steps, ladders and areas with a railing or structure at least 12" high are excluded from this requirement.

Standard Warranty

The apparatus manufacturer shall provide a full 1 year standard warranty. All components manufactured by the apparatus manufacturer shall be covered against defects in materials or workmanship for a 1 year period. All components covered by separate suppliers such as engines, transmissions, tires, and batteries shall maintain the warranty as provided by the component supplier. A copy of the warranty document shall be provided with the proposal.

10 Year/100,000 Mile Structural Warranty

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

The apparatus manufacturer shall provide a comprehensive 10 year/100,000 mile structural warranty. This warranty shall cover all structural components of the cab and/or body manufactured by the apparatus manufacturer against defects in materials or workmanship for 10 years or 100,000 miles, whichever occurs first. Excluded from this warranty are all hardware, mechanical items, electrical items, or paint finishes. A copy of the warranty document shall be provided with the proposal.

10 Year Stainless Steel Plumbing Warranty

The apparatus manufacturer shall provide a full 10-year stainless steel plumbing components warranty. This warranty shall cover defects in materials or workmanship of apparatus manufacturer designed foam/water plumbing system stainless steel components for 10 years. A copy of the warranty document shall be provided with the proposal.

10 Year Paint and Corrosion Warranty

The apparatus manufacturer shall provide a 10-year limited paint and corrosion perforation warranty. This warranty shall cover paint peeling, cracking, blistering, and corrosion provided the vehicle is used in a normal and reasonable manner.

The paint shall be prorated for 10 years as follows:

Topcoat & Appearance: Gloss, Color Retention, Cracking		Coating System, Adhesion & Corrosion: Includes Dissimilar metal corrosion, Flaking, Blistering, Bubbling	
0 to 72 months	100%	0 to 36 months	100%
73 to 120 months	50%	37 to 84 months	50%
		85 to 120 months	25%

Corrosion perforation shall be covered 100% for 10 years. Corrosion perforation is defined as complete penetration through the exterior metal of the apparatus.

The warranty period shall begin upon delivery of the apparatus to the original user-purchaser. A copy of the warranty document shall be provided with the proposal.

UV paint fade shall be covered in a separate warranty supplied by Akzo Nobel (Sikkens) and shall be for a minimum of 10 years.

25 Year Frame Rail Corrosion Warranty

The chassis manufacturer shall provide a 25 year corrosion warranty on the chassis frame rails. This warranty shall cover the chassis frame rails, including frame rail liners (if equipped), for a period of 25 years after the date on which the vehicle is delivered to the original purchaser. A copy of the warranty document shall be provided with the proposal. Please refer to warranty document for complete details and exclusions.

KINGSTON FIRE DISTRICT
SPECIFICATIONS FOR 1500 GPM CUSTOM PUMPER

20 Year Frame Components Corrosion Warranty

The chassis manufacturer shall provide a 20 year corrosion warranty on the galvanized chassis frame components. This warranty shall cover the front frame extensions, chassis crossmembers (from engine rearward), battery tray brackets and rear underbody support (if applicable) for a period of 20 years after the date on which the vehicle is delivered to the original purchaser. A copy of the warranty document shall be provided with the proposal. Please refer to warranty document for complete details and exclusions.

Lifetime Frame Warranty

The apparatus manufacturer shall provide a full lifetime frame structural warranty. This warranty shall cover all apparatus manufacturer designed frame, frame members, and cross-members against defects in materials or workmanship for the lifetime of the covered apparatus. A copy of the warranty document shall be provided with the proposal. Frame warranties that do not cover cross-members for the life of the vehicle shall not be acceptable.

Additional Equipment

Mounting allowance for dept. supplied equipment - \$15,000

Shelf/tray allowance - \$15,000

Mount (4) dept. supplied radios

6" NH x 5" storz intake adapter

4" NH x 5" storz adapter